SOLUS - SPECIFICATION

Foundation – Pile foundation

Structure- RCC frame structure

Outdoor Finish- Weather coat paint

Thickness of outer walls of the flats - 200 mm

Thickness of inner walls of the flats - 100 mm

Wall & Ceiling - POP finish

Flooring - Vitrified tiles

Doors - 32 mm flash door

Height of Doors - 2100 mm

Height of windows- 1800 mm

Door frame - Sal Wood

Window - Aluminum sliding windows

Sanitary wares - Varmora or equivalent brand

Sanitary Fitting- Essco or equivalent brand

Electrical Fitting – Concealed wiring with provision of modular switches

(Colors or equivalent brand)

Kitchen fittings- Stainless steel sink, provision of water filter point

Provision of Chimney and Exhaust point - Yes

Provision for AC's- for 2 BHK in Master bed room for 3 BHK & 4 BHK –Master

Bed Room & One Common bed room

Provision for hot & cold water line in Shower area only in toilet - yes

Water filtration plant in the project - yes

Roof top treatment - waterproofing

Source of water in the project – Deep Tubewell

Provision for generators for the flats (On Extra Cost) – Yes

Firefighting arrangements in the project – As per fire department Norms

Earth quake resistant - Yes

Pollution Clearance-Yes

For SRIJAN RESIDENCY LLP

(Authorized Signatory)