STATE LEVEL ENVIRONMENT IMPACT ASSESSMENT AUTHORITY

Pranisampad Bhavan, LB-2, 5th Floor, Sector III, Salt Lake, Kolkata - 700 106

Web Portal: www.environmentwb.gov.in

No. 991 /EN/T-II-1/085/2017

Date:

24th April, 2018

To M/s Rishinox Buildwell LLP, DLF Glleria, Unit 306, Premises No. 02-0124, Action Area – 1B, New Town, Kolkata – 700 156.

Sub: Stipulated conditions for getting Environmental Clearance for the proposed housing complex at Mouza – Kalikapur, J.L. No. 40, P.O. & P.S. – Rajarhat, Patharghata G.P., Dist. North 24 Parganas, Kolkata – 700135, West Bengal.

Sir.

This has a reference to your application submitted on 12.12.2017 for environmental clearance for the proposed housing complex at Mouza – Kalikapur, J.L. No. 40, P.O. & P.S. – Rajarhat, Patharghata G.P., Dist. North 24 Parganas, Kolkata – 700135, West Bengal and presentation made by you before SEAC on 18.01.2018.

Based on your application for environmental clearance and presentation made by you, SEAC in its meeting dated 24.03.2018 has recommended a list of stipulated conditions for the project proposal.

SEIAA in the meeting dated 17.04.2018 approved the stipulated conditions for Environmental Clearance proposed by SEAC (copy of which is enclosed herewith).

You are requested to prepare the construction plan incorporating those conditions before submission of the same for building plan approval. The sanctioned building plan, along with a comparative statement of salient features between those in stipulated conditions and sanctioned plan may kindly be submitted in the secretariat of SEAC at Paribesh Bhavan, Salt Lake. The SEIAA shall consider the case only when it is ensured that the conditions listed in the enclosure have been properly addressed in the building plan.

Member Secretary, SEIAA


No. 991 /EN/T-II-1/085/2017

Date:

24th April, 2018

Copy forwarded for information to the Secretary, State Level Expert Appraisal Committee.

Sd/-Member Secretary, SEIAA



Name of Environmental Consultant - M/s. Centre For Sustainable Development

This has reference to the application for environmental clearance dated 28/12/2017 along with FORM I, FORM IA and other documents on the above referred project. This also refers to the letter dated 27/02/2018 for submission of clarification.

- This is a proposal for construction of a residential complex consisting of two phases: Phase 1 2 Nos. B+LG+UG+24 & 2 Nos. B+LG+UG+23; Phase 2 - 1 No. B+LG+UG+3PD+22 storied buildings. Total built up area of the project (Phases 1 & 2 combined) is 86,275.409 sq. m. and the total no. of flats will be 727.
- 2. The above proposal has been considered in the 152nd and 154th SEAC meetings held on 18/01/2018 and 24/03/2018 respectively.
- 3. Salient features of the proposed project are as follows -

Salient Features	Phase - I	Phase - II	Total Scenario of Both Phases (Phases - I + II)
Land Area	19,995.56 sq.m (as per deed) 20,150 sq.m (as per survey) 17,073.42 sq.m (net land area after gift for road widening)		19,995.56 sq.m (as per deed) 20,150 sq.m (as per survey) 17,073.42 sq.m (net land area after gift for road widening)
No. of Flat	551	176 LG N PV 0	727
No. of Residential Block	B + LG + UG + 24 storied = 2 Nos. B + LG + UG + 23 storied = 2 Nos.	B + LG + UG + 3PD + 22 storied = 1 No.	B + LG + UG + 24 storied = 2 Nos. B + LG + UG + 23 storied = 2 Nos. B + LG + UG + 3PD + 22 storied = 1 No.
Expected Population	Resident = 2385 persons Floating = 238 persons Service Staff = 40 persons Total = 2663 persons	Resident = 836 persons Floating = 84 persons Club Users = 322 persons Service Staff = 10 persons Total = 1252 persons	Resident = 3221 persons Floating = 322 persons Club Users = 322 persons Service Staff = 50 persons Total = 3915 persons
Total Water Requirement (Operation Stage)	363 KLD	130 KLD	493 KLD
Freshwater Requirement (G/W Supply)	218 KLD	80 KLD	298 KLD
Wastewater Generated	262 KLD (to be treated in STP)	96 KLD (to be treated in STP)	358 KLD (to be treated in STP)



Relevant parts of the minutes of the 154th SEAC meeting for stipulating conditions for environmental clearance of proposed housing complex by M/s. Rishinox Buildwell LLP at Mouza - Kalikapur, JL No. 40, P.O. & P.S. - Rajarhat, Kolkata - 700 135, Patharghata G.P., Dist - North 24 Parganas, West Bengal. S. Name of Environmental Consultant - M/s. Centre For Sustainable Development

Salient Features	Phase - I	Phase - II	Total Scenario of Both Phases (Phases - I + II)
	D.L.J.W. 1		
Wastewater Treated	236 KLD	86 KLD	322 KLD
Wastewater Recycled	139 KLD	48 KLD	187 KLD
Wastewater Discharged	97 KLD (to panchayat drain)	38 KLD (to panchayat drain)	135 KLD (to panchayat drain)
Solid Waste Disposal	1.37 Tonne/day (panchayat)	0.52 Tonne/day (panchayat)	1.89 Tonne/day (panchayat)
Total Built Up Area	63,099.329 sq.m	23,176.08 sq.m	86,275.409 sq.m
Ground Coverage	कर कर विश्वयाद्वास्त्र । स्थापन	The Av	7045.234 sq.m (41.26% of net land area)
Total Paved Area	*es		4259.43 sq.m (24.95% of land area)
Semi Paved Area	.0 KV/0 t		2918.043 sq.m (17.09% of land area)
Green Area for Plantation	1.80		3493.25 sq.m (20.46% of land area)
Area under Service	4 1x 20 1 1		320.053 sq.m (1.87% of land area)
Internal Road & Pavement	es es es		2800.413 sq.m (16.40% of land area)
Other Green Area	Call at the stage	5) ×	495.86 sq.m (2.90% of land area)
No. of Proposed Trees	200	50	250
No. of Parking Space Proposed	554 (Covered = 432 Open = 122)	176 (Covered = 146 Open = 30)	730 (Covered = 578, Open = 152)
Total Power Requirement	1886.4 KW (WBSEDCL)	637.2 KW (WBSEDCL)	2524 KW (WBSEDCL)
Back up Power	(1 X 500 KVA + 1 X 250 KVA) D.G. Sets	(1 X 250 KVA) D.G. Sets	(1 X 500 KVA + 2 X 250 KVA) D.G. Sets



Name of Environmental Consultant - M/s. Centre For Sustainable Development

4. The State Level Expert Appraisal Committee, West Bengal, hereby, proposes the stipulated conditions for environmental clearance as per the provision of Environmental Impact Assessment Notification 2006 and the subsequent amendments, on the basis of above mentioned features along with other details submitted to SEIAA, subject to strict compliance of the terms and conditions (whichever applicable at building sanction stage) mentioned below.

Part A - SPECIFIC CONDITIONS

I. Construction Phase

Facility of labourers during construction: -

- i. Provision of drinking water, wastewater disposal and solid waste management should be ensured for labour camps. Water usage during construction should be optimized to avoid any wastage.
- ii. Proper sanitation facilities should be provided for construction workers to ensure environmental sanitation. Sewage generated from the areas occupied by the construction labourers have to be directed into the existing sewage drain of the area. In case of non-availability of the sewer system, an onsite treatment system has to be provided.
- iii. The scaffolds, stairs and platforms for construction works and the workers must be secured as far as possible to prevent any accident.
- iv. Health and safety of the workers should be ensured during construction. Personnel protective equipment like shoes, helmets, earmuffs, earplugs etc. should be provided to the workers. For vibration control damped tools must be used and the number of hours that a worker uses them must be limited. The Management must ensure that the workers put them while doing work that needs such protection, if any.
- v. Rest and convenience shelter for workers with crèche facility, if required, particularly women, must be provided with proper toilet facilities.

Steps to avoid disturbance during construction: -

- i. The proponent should abide by the Construction and Demolition Waste Management Rules, 2016. All the topsoil excavated during construction activities should be under cover/stored by retaining walls for use in horticulture / landscape development within the project site. Adequate erosion and sediment control measures to be adopted before ensuing construction activities.
- ii. Prior permission should be obtained from the competent authority for demolition of the existing structure, if any. Waste recycling plans should be developed for prior to beginning of demolition and construction activity. The plans should identify wastes to be generated and designate handling, recycling and disposal method to be followed.
- iii. Disposal of muck including excavated material during construction phase should not create any adverse effects on the neighbouring communities and disposed off taking the necessary precautions for general safety and health aspects.
- iv. Diesel generator sets during construction phase should have acoustic enclosures and should conform to E(P) Rules prescribed for air and noise emission standards.
- v. Vehicles / equipment deployed during construction phase should be in good condition and should conform to applicable air and noise emission standards and should be operated only during nonpeaking hours.
- vi. Ambient noise levels should conform to residential standards both during day and night. Fortnightly monitoring of ambient air quality (SPM, SO₂ and NOx) and equivalent noise levels should be ensured during construction phase.
- vii. Construction spoils including bituminous material and other hazardous materials including oil from construction equipments must not be allowed to contaminate watercourses and the dumpsites for such material must be secured so that they should not leach into the ground water. If necessary, oil trap should be installed where there is deployment of heavy machineries.

and

Secretary, State Expert Appraisal Committee, West Bengal

Page 3 of 10

Name of Environmental Consultant - M/s. Centre For Sustainable Development

- viii. Regular supervision of the above and other measures should be in place all through the construction phase so as to avoid disturbance to the surroundings. Discomfort in the neighbourhood due to the proposed project activity should be minimized as far as practicable.
- ix. Loading and unloading operations should not be carried out in open areas and should be preferably done during day time, if there is any major settlement in the surrounding areas. The construction activities including piling work, Operation of Ready Mix Plant and Vibrator etc. should not be carried out during the night time (10 P.M. to 6 A.M.). Only essential operations, if any, may be carried out for a limited period during nighttime.

x. The proponent must ensure that no driven piles shall be proposed for this project, if there is any major settlement in the surrounding areas.

- xi. 15m-screen and adequate sprinkler arrangement shall be provided. Care should be taken to keep all material storages adequately covered and contained so that they are not exposed to winds.
- xii. Use of Ready-Mix concrete is recommended for this project.
- xiii. Adequate measures to be adopted to avoid wastage of water for curing of concrete structures.
- xiv. Adequate mitigative measures should be adopted to control dust emissions, noise and vibrations from construction activities. Vehicles and construction machineries should be properly maintained. Vehicles should conform to Pollution under control (PUC) norms.
- xv. Locally available materials with less transportation cost should be used preferably.
- xvi. Promotion of use of cleaner fuel and fuel quality improvement should be done. Excessive energy consumption and fuel usage should be avoided.
- xvii. Accumulation / stagnation of water should be avoided to ensure vector control.

Selection of materials for better energy efficiency:-

- i. Use of energy efficient construction materials should be ensured to achieve the desired thermal comfort.
- ii. Design layout should ensure adequate solar access and ventilation. Proper planning and window design for daylight integration should be considered.
- iii. Fly Ash is to be used for construction as per Notification No. S.O. 763(E) dated 14.09.1999 amended vide Notification No. S.O. 979(E) dated 27.8.2003, S.O. 2804(E) dated 03.11.2009 and S.O.254(E) dated 25.01.2016 of the Ministry of Environment & Forests, Govt. of India.
- iv. Construction should conform to the requirements of local seismic regulations. The project proponent should obtain permission for the plans and designs including structural design, standard and specifications from concerned authority.
- v. Construction technologies that require less material and possess high strength should be adopted. Materials with low embodied energy and high strength should be used preferably.
- vi. The building will be constructed and provisioned to use natural sunlight to the maximum during the day time, during use.
- vii. Use of alternate building materials and alternate construction techniques should be considered apart from the conventional materials and methods. Use of hollow unit masonry should be considered.
- viii. Use of energy efficient lighting systems e.g. High Pressure Sodium Vapour (HPSV) Lamps, LED etc. should be promoted. Solar energy should be used for outdoor lighting. Adequate no. of solar lights should be installed for external lighting as per norms. All common area lighting will be LED system.
- ix. Solar water heating arrangement will be done for water heating in canteen area as proposed.
- x. Passive solar cooling to be incorporated in building design. Buildings should be oriented for ensuring natural ventilation and day lighting.
- xi. Proper insulation of roof should be provided to achieve desired thermal comfort. Use of light coloured, reflective roofs having an SRI (solar reflectance index) of 50% or more should be incorporated.

a a h

Name of Environmental Consultant - M/s. Centre For Sustainable Development

- xii. Use of high albedo or reflective pavements to keep parking lots, pavements and inside roads cool should be incorporated.
- xiii. Guidelines to the occupants should include usage efficiency measures such as energy efficient lighting and water efficient system.
- xiv. Reduce hard paving-onsite (open area surrounding building premises) and/or provide shade on hard paved surfaces to minimize heat island effect and imperviousness of the site.
- xv. Adequate open space, greenery and water bodies to be provided as per rules.
- xvi. Any proposed building with air-conditioning facility should follow the norms proposed in the ECBC regulations framed by the Bureau of Energy Efficiency. Use of chillers will be CFC & HCFC free.
- xvii. Restrict the use of glazed surface as per National Building Code 2005 and as amended thereafter.
- xviii. At least 1% of total demand load to be met from solar power source.

Water Body Conservation: -

i. Existing water body (if any) should not be lined and their embankments should not be cemented. The water body is to be kept in natural conditions without disturbing the ecological habitat. The area and location of the water body should be incorporated in the santage and building plan of the concerned authority.

Land Character: -

No construction activity is permitted under any circumstances on any designated water body or any plot of land characterized as wetland.

Plantation Proposal: -

- The unit should strictly abide by The West Bengal Trees (Protection and Conservation in Non-Forest Areas) Act, 2006 and subsequent rules. The proponent should undertake plantation of trees over at least 20% of the total area.
- ii. No tree can be felled without prior permission from the Tree Cutting Authority constituted as per the West Bengal Trees (Protection and Conservation in Non-Forest Areas) Act, 2006 and subsequent rules.
- iii. The proponent should plant at least 250 trees as proposed. The landscape planning should include plantation of native species. The species with heavy foliage, broad leaves and wide canopy cover are desirable. Water intensive and/or invasive species should not be used for landscaping.
- iv. Provision for Roof Top Gardening is mandatory.

Water supply: -

 Water requirement during construction phase shall be met from ground water supply. Ground water should not be abstracted without prior permission of the Competent Authority as per the West Bengal Ground Water Resources (Management, Control and Regulation) Act, 2005.

Sewage Treatment Plant: -

As per the proposal during construction phase construction water must be treated and reused.
 Domestic waste water generated during construction phase must be treated in a septic tank followed by soak pit.

Storm water Management & Mitigation of Heat Island Effect: -

- Imperviousness of the site shall not exceed the NBC (National Building Code 2005 and as amended thereafter) standards for imperviousness factor applicable to different types of area.
- ii. Total paved area of site under parking, roads, paths or any other use should not exceed 25% of the site area.

ala

Secretary, State Expert Appraisal Committee, Senga

Page 5 of 10

Name of Environmental Consultant - M/s. Centre For Sustainable Development

- iii. Minimum 50% of paved area on site should have pervious paving or shaded under vegetation or topped with finish having solar reflectance of 0.5 or higher.
- iv. Adequate storm water drainage network to be designed for the project without disturbing the surrounding settlements. Storm water management plan should be implemented so as to prevent sudden discharge of excessive volumes of storm water to the receiving waters thus reducing the shock load on the drainage system and impact on receiving water body.
- v. Disruption to the natural hydrology of the site should be minimised by reducing impervious cover, increasing on site infiltration and managing storm water runoff.
- vi. Heat island effect should be inimized by use of shading or reflective surfaces, mainly the surfaces that contribute to the heat island effect i.e. streets, sidewalks, parking lots and buildings. White roofs should be provided in the buildings.

Rain Water Harvesting Scheme: -

- i. A rain water harvesting plan needs to be designed where the recharge bores of minimum one recharge bore per 5,000 square meters of built up area and storage capacity of minimum one day of total fresh water requirement shall be provided. Detailed plan and sections of the storage tank with reference to the building line and levels to be submitted.
- ii. The proponent must collect rainwater from roof-top catchments and reuse for various purposes after necessary cleaning. Adequate retention time and storage provisions should be provided for harvesting rainwater.
- iii. The proponent must ensure proper depth of recharge well for ground water recharging.
- iv. Adequate firefighting storage should be provided as per norms.

Solid Waste Management: -

- Conform to the guidelines on Environment Management of Construction & Demolition Waste by CPCB, March 2017.
- ii. Adequate provision shall be made for storage and segregation of solid waste and adequate means of access shall be provided.
- iii. All construction and demolition debris shall be stored at the site (and not dumped on the roads or open spaces outside) before they are properly disposed. All demolition and construction waste shall be managed as per the provisions of the Construction and Demolition Waste Rules, 2016.

Transport Management: -

- Both internal and external traffic planning and management should be adequate to ensure uninterrupted traffic movement in the area during construction as well as operation phase.
- ii. The design of service road and the entry and exit from the project area should conform to the norms & standards of competent authority for traffic management. Bell mouth type arrangement should be made at the entry & exit. Proper traffic management plan should be adopted in consultation with Traffic authorities.
- iii. Clarified Wastewater will be used for sprinkling water on the unpaved internal roads on a regular basis

Others: -

- Notification G.S.R. 94(E) dated 25.01.2018 issued by MoEF & CC, Government of India should be complied with.
- ii. Conform to the clause mentioned in the "Manual and standards for EC for large construction projects" published by MoEF & CC. Covernment of India.



Name of Environmental Consultant - M/s. Centre For Sustainable Development

iii. Incorporate details of all dimensions and functional, positional arrangement of STP, Compost plant, Rainwater harvesting reservoir in the approved plan.

iv. Scaled up drawings (both plan and section) of STP, compost plant and rainwater harvesting tank showing portion of adjacent areas mentioning the levels and entry/exit to the facilities to be submitted.

v. Location of the said facilities in the floor plan mentioning the levels should be submitted.

vi. Final site plan (in conformity with the final approved plan) showing Land use distribution with polyline and corresponding legend mentioning Area and Percentage of each use both in soft (Auto CAD 2010) & hard copy formats to be submitted.

vii. All mandatory approvals and permission as required from Director of Explosives, Fire Department etc. should be obtained.

viii. Provision of Effective Controls and Building Management Systems such as Automatic Fire Alarm and Fire Detection and Suppression System etc. must be ensured.

ix. Efficient management of indoor air quality must be ensured for health and safety of the users.

- x. Adequate measures to be adopted for water conservation during construction and operation stage. Use of efficient irrigation equipment, evaporative cooling unit in air-conditioning system etc should be considered.
- xi. Rest room facilities should be provided for service population.

xii. Adequate access to fire tenders should be provided.

II. Operation Phase

Water supply: -

- i. Water requirement shall be met from ground water supply. Ground water should not be abstracted without prior permission of the competent authority as per the West Bengal Ground Water Resources (Management, Control and Regulation) Act, 2005.
- ii. Use of water meter conforming to ISO standards should be installed at the inlet point of water uptake to monitor the daily water consumption. Use of water efficient devices / fixtures and appliances should be promoted. Installation of dual flushing system should be considered to conserve water.
- iii. The proponent must practice rainwater harvesting on regular basis.

Sewage Treatment Plant: -

- i. As per the proposal submitted by the proponent, waste water shall be treated in STP. Treated waste water shall be partly reused for landscaping, flushing and car washing and rest will be discharged to drain. Necessary permission from the Competent Authority to be obtained.
- ii. Reuse of treated wastewater should be carried out as proposed.

Emission from Diesel Generator Set: -

- Noise barriers will be provided at appropriate locations so as to ensure that the noise levels do not
 exceed the prescribed standards. Diesel generator sets should be provided with integral acoustic
 enclosure at the manufacturing stage itself as per CPCB norms.
- ii. The stack height and emissions from D.G. sets should conform to the norms of Central Pollution Control Board. The certification of space design for DG sets should be done by competent authority.

Ensure Energy Efficiency: -

 Use of energy efficient construction materials to achieve the desired thermal comfort should be incorporated. The desired level of R and U factors must be achieved. U factor for the top roof should

a and

Secretary, State Expert Appraisal Committee, West Bengal

Page 7 of 10

Name of Environmental Consultant - M/s. Centre For Sustainable Development

not exceed 0.4 Watt/sq.m/degree centigrade with appropriate modifications of specifications and building technologies. The provisions of National Building Code 2005 and as amended thereafter should be strictly followed.

- ii. Use of energy efficient electrical systems should be promoted. High efficiency lamps with electronic ballasts should be used.
- iii. Energy efficient Motors value properly rated Transformers should be installed. Manufacturer's certificate to this effect shall be obtained and kept on record. Backup power supply should be based on cleaner fuel.
- iv. The power cabling shall be adequately sized as to maintain the distribution losses not to exceed 1% of the total power usage. Record of transmission losses shall be maintained. The proponent shall install permanent electrical metering to record demand (kVA), energy (kWh) and total power factor.
- v. At least 1% of total demand load to be met from solar power source.

Transport Management: -

- i. Use of public mode of transportation should be promoted. Use of the least polluting type of transportation should be promoted. Adequate parking space should be provided as per norms.
- ii. Pathways should be covered or shadowed by tree canopy as far as practicable. Transport system should be such that traffic will be calm in neighbourhoods. Traffic within the project site should be restricted by regulation. Adequate vertical and horizontal clearances of overhead electric power and telecommunication lines should be provided.

Solid Waste Management: -

- i. The proponent should abide by the Solid Waste Management Rules, 2016. The proponent must develop the Solid Waste Management and Disposal Scheme ensuring storage and segregation of biodegradable and non-biodegradable wastes. The solid waste is to be disposed off in consultation with concerned local body.
- ii. The proponent should provide different coloured bins for different categories of waste and ensure complete segregation of biodegradable and non-biodegradable wastes. The solid waste from different collection and storage bins should be finally collected at transfer stations. Further segregation will be done at transfer stations to collect recyclables such as plastic, polythene, glass, metals, textiles, rubbers, leathers, paper etc. Separate compartments shall be provided for each type of recyclables.
- iii. The proponent should abide by the Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016. Collection and storage of hazardous wastes during Pre-construction and Post-construction activity should be planned properly. The expected hazardous wastes should be disposed off separately as per the Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016.
- iv. Spent oil from DG Sets should be stored in HDPE drums in isolated covered facility and disposed off as per the Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016. Spent oil from DG Sets should be disposed of through registered recyclers only.

Others:-

- i. The implementation of Environmental Management Plan should be carried out, as proposed. Regular monitoring should be carried out during construction and operation phases.
- ii. The project proponent should provide guidelines to the users to ensure conservation of energy and water. In-house environmental awareness campaigns should be carried out at regular intervals to ensure environmental protection.

aav

Name of Environmental Consultant - M/s. Centre For Sustainable Development

- iii. Firefighting systems should be designed in compliance with the WBFS and NBC norms. Preventive measures should be adopted for Risk & Disaster Management as per the provisions of the National Building Code 2005 and as amended thereafter.
- iv. At least 2.5% of the total cost of the project shall be earmarked towards the Enterprise Social Commitment (ESC) based on local needs and action plan with financial and physical break-up shall be prepared and submitted. Implementation of such program shall be ensured accordingly in a time bound manner.
- v. The proponent should abide by the Direction issued by the Department of Environment, Government of West Bengal, vide No. EN/3170/T-IV-7/001/2009 dated 10.12.2009.
- vi. Environmental Management Information System shall be maintained properly.
- vii. The proponent should restrict the use of glazed surface as per National Building Code 2005 and as amended thereafter

Miles I is

A. L. ..

Part-B GENERAL CONDITIONS

- 1. The environmental safeguards contained in the EMP Report should be implemented.
- All the conditions, liabilities and legal provisions contained in the Stipulated conditions for Environmental Clearance (SCEC) shall be equally applicable to the successor management of the project in the event of the project proponent transferring the ownership, maintenance of management of the project to any other entity.
- 3. All the labourers to be engaged for construction works should be screened for health and adequately treated before issue of work permits. Provision should be made for the supply of kerosene or cooking gas to the labourers during construction phase.
- The project proponent should make financial provision in the total budget of the project for implementation of the suggested safeguard measures.
- 5. In case of any violation of the conditions laid down in this SCEC, Section 16 of The Environment (Protection) Act, 1986, will be applicable. In case of any charge(s) in the scope of the project, the project would require a fresh appraisal by the SEAC, West Bengal.
- 6. The State Expert Appraisal Committee, West Bengal reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the stipulated conditions for environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time-bound and satisfactory manner.
- 7. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Civil Aviation Department (if required) etc. shall be obtained by project proponents from the competent authorities.
- 8. Provision for incorporation of appropriate conditions in the Sale Agreement / Deed, for ensuring sustained Operation and Maintenance (O&M) of the common facilities (STP, Rainwater harvesting system, Solid waste management system, Solar street lights etc.) even after transfer of ownership of the project, should be made in explicit and transparent manner.
- 9. These stipulations would be enforced among others under the provisions of the Water (Prevention & Control of Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification 2006 including the amendments and clarification circulars.

aar

Secretary, State Expert Appraisal Committee, West Bengal

Page 9 of 10



Name of Environmental Consultant - M/s. Centre For Sustainable Development

10. The final Environmental Clearance shall be accorded by the State Environmental Impact Assessment Authority, West Bengal after submission of master site plan of the whole project sanctioned by the concerned municipality incorporating all the salient features of the stipulated conditions for environmental clearance and necessary documents and consideration of the same by the State Level Expert Appraisal Committee, West Bengal. The area statement as well as detailed building profile, parking spaces etc., as proposed in the salient features, should be clearly mentioned in the sanctioned Master Plan.

aa

(Sandipan Mukherjee, IFS)
Secretary, State Expert Appraisal Committee,
West Bengal

(Dr. Tapan Kumar Mukherjee) Chairman, State Expert Appraisal Committee, West Bengal

