DEVIATION WOULD MEAN DEMOLITION

RESIDENTIAL BUILDING

"CONSTRUCTION SITE SHALL BE MAINTAINED" TO PREVENT MOSQUITO BREEDING AS REQUIRED U/S 496(1) & (2) OF CMC ACT1980, IN SUCH MANNER SO THAT ALL WATER COLLECTIONS PARTICULARLY LIFE WELLS, VATS, BASEMENT SURING SITES OPEN RECEPTACLES ETO AS EMPITED COMPLETELY TWICE & WEAR"

No rain water pipe should be fixed or discharged on Road or Footpath. Drainage plan should be submitted at the Borough Executive Engineer's Office and the senction obtained before proceeding with the drainage work

Before starting any Construction the site must conform with plans sanctioned and all the conditions as proposed in the plan should be fulfilled

The validity of the written permission to execute the work is subject to the above conditions

A suitable pump has to be provided i.e. pumping unfiltered water for the distribution to the flushing cisterns and urinals in the building incase unfiltered water from street main is not available.

Plan for Water Supply arrangement including SEMILI G. & O. H. reservoirs should be submitted at the Office of the Ex-Engineer Water Supply and the sanction obtained before proceeding with the work of Water Supply any deviation may lead to disconnection/demolition.

> CHECKED AND VERIFIED Sulver A.E.(C)/S.A.E.(C)

This is to let you know that the onus of preventing mosquito breeding at the said construction size rimatily rests with you and hence you are hereby requested to undertake the following pre-cases measures on your own on a regular basis to keep the site fee of mosquito larvae.

Figure people and a party trade to be a proper trade of the site free of mosquito larvae.

Empty each and every water storage container/reservoir at a weekly interval.

Empty each and every water storage container/reservoir at a weekly interval.
 If you face any problem in emptying water containers/ reservoirs, please cause to sprinkle kerosene/ diesel/ MLO (mosquito larvieidal ail) on their water surfaces @ of 2.5-3 littles per 100 sq m surface area at weekly intervals.
 For carrying out the need-based larvieidal spray with any of the said 3 materials at your construction site, please procure 1 or 2 Knapsack Sprayers (16-litre capacity) from the open market and select 1-3 field workers from your end and accomplish the job by employing their services at a weekly interval.
 Tachvical knowshow for surinkling/ spraying may be obtained from the visiting Vector.

employing their services at a weekly interval.
 Technical knowhow for sprinkling/ spraying may be obtained from the visiting Vector Control Team of KMC; the team will keep a close watch on your construction site.
 If any sort of violation on your part with regard to implementation of the proposed antimosquito guidelines is found, logal steps will be resorted to by the KMC as per the systems record.

Please cooperate and help the Health Department of KMC prevent transmission of mo diseases in the city of Kolkata

Non Commencement of Erection/ Re-Erection within Two Year will Require Fresh Application for Sanction.

All Building Materials to necessary & construction should conform's to standered specified in the National Building Code of India.

Design of all Structural Members including that of the foundation should conform to Standards specified in the National Building Code of India.



CERTIFIED COPY

KOLKATA MUNICIPAL CORPORATION BUILDING DEPARTMENTS CERTIFIED COPY OF B.S. PLAN Borough No Asarkow Executive Enginee 15 Assistant Engineer

> Necessary steps should be taken for the safety of the lives of the adjoining public and private properties during construction.

Structural plan and design calculation as submitted by the structural engineer have been kept with B. P. No. 2018 130 27 5 Date 11/01/19 for record of the Kolkata Municipal Corporation without verification No. deviation from the submitted structural plan should be made at the time of erection without submitting fresh structural plan along with design calculation and stall thy certificate in the prescribed from, necessary steps should be taken for the safety of the adjoining premises public and private properties and safety of human life during construction

Asstr-Engineer/Technical Advisor / Executive Engineer BOROUGH NO .- XIII, XIV

- tion area/buildings with geotextile fabric installing dust barriers, or other actions; as
- b) Apply water and maintain solls in a visible damp or crusted condition for temporary stabilization
- c) Apply water prior to leveling or any other earth moving activity to keep the soil moist throughout the
- d) Umit vehicle speeds to 15 mph on the work site

- e) Clean wheels and undercarriage of houl trucks prior to leaving construction site.
 f) Apply and maintain dust suppressant on houl routes.
 g) Apply a cover or screen to stockpiles and stabilize stockpiles at completion of activity by water and
- maintain a dust palliative to all order surfaces of the stockpiles;

 h) Stabilize surface soils where loaders, support equipment and vehicles will operate by using water and maintain surface soils in a stabilized condition where loaders, support equipment and vehicles will
- i) Stabilize adjicent disturbed soils following paying activities with immediate landscaping activity or
- j) Mointain dust control during working hours and clean track out from paved surfaces at the end of the work shift/day. Track one must now extend 50 feet or more and must be cleaned daily, at the
- k) Stabilize sloping surfaces using soil binders until vegetation or ground cover can effectively stabilize the slope, Disposal of debris in consultation with the local authorities following proper environmental
- nanagement practice. in) During construction work, including cutting of marbles, ambient noise level should not exceed more than 65 dB(A).
- B. Practices to be discarded for pollution free Environment:
- Don't dispose of debris indiscriminately,
- b) Don't allow the rehicles to run at high speed within the work site.
 - tion't cut materials without proper dust control/noise control facility. Don't keep materials without effective cover.
- e) Don't allow access in the work area except workers to limit soil disturbance and prevent access by
- fencing, ditches, vegetation, berms or other suitable barrier

 f) Don't leave the soil, sand and cement stack uncovered.
- Don't keep materials or debris on the roads or paven ents
- b) Burning of old tyres in hot mix plant as a fuel during construction and repair of the roads for cuclting coal far should be distanted:

