

Commencement of Erection/ rection within Five year will re Fresh Application for Sanction ssary steps should be taken ie safety of the lives of the ining public and private erties during construction.

RESIDENTIAL BUILDING

Sierfilfia

ruction may be at the

a) Wrap construction area/buildings with geotextile fabric installing dust be appropriete for the location.

Apply water and maintain solls in a visible damp or crusted condition for te (Apply water prior to leveling or any other earth moving activity to keep the process:

Apply water prior to leveling or any other earth moving activity to keep the process:

Apply a cover or streen to stockpiles and stabilize, stockpiles and attained, stockpiles and attained, stockpiles and attained, stockpiles will maintain surface soils where locaders, support equipment and vehicles will maintain surface soils where locaders, support equipment and vehicles will maintain surface soils in a stabilized condition where loaders, support operate:

Stabilize adjacent disturbed soils following paving activities with immerialisation of vegetative or rock cover:

Installation of vegetative or rock cover:

Maintain stoping surfaces using working hours and clean track-out from pav work six.

Track out must now extend 50 feet or more and minimums.

Track out must now extend 50 feet or more and minimums.

Track out must now extend 50 feet or more and minimums.

The slope.

Disposal of theirs in consultation with the local authorities follo management practices using soil binders until vegetation or ground on the slope.

Disposal of theirs in consultation with the local authorities follo management practices to run at high speed within the work site.

Disposal of debris in consultation with the local authorities follo management practices to run at high speed within the work site.

Disposal follow the vehicles to run at high speed within the work site.

Disposal of debris indiscriminately.

Disposal situation work, including gutting of marbles, ambient noise in the soll debris on the roads or pavements.

Disposal situation work and cement stack uncoverted.

English process of the work area except workers to limit soil disturbancing of each stabilized and cement stack uncoverted.

Burning of old tyras in het mich plant as fuel during constru Elimit withfice speeds to 15 mpb on the work site.

Clean wheels and undercarriage of haul trucks prior to leaving construction site.

Apply a cover or screen to stockpillas and stabilize stockpillas at completion of activity by water and maintain a stabl pellitative to all outer surfaces of the stockpillas at completion of activity by water and maintain a stabl pellitative to all outer surfaces of the stockpillas at completion of activity by water and maintain surface soils where loaders, support equipment and vehicles will operate:

Stabilize surface soils in a stabilized condition where loaders, support equipment and rehicles will operate:

Stabilize adjacent disturbed soils following paving activities with immediate landscaping activity or installation of vegetative or rock cover:

Maintain of vegetative or rock cover:

Maintain of regetative or rock cover:

Maintain of regetative or rock cover:

Track out must now extend 50 feet or more and must be cleaned daily, at the minimum.

Stabilize stoping surfaces using soil binders until vegetation or ground cover can effectively stabilize of debris in consultation with the local authorities following proper environmental management practice.

Disposal of debris in consultation with the local authorities following proper environmental management practice.

During construction work, including cutting of marbles, ambient noise level should not exceed more than 65 d8(A).

reps.