STATE LEVEL ENVIRONMENT IMPACT ASSESSMENT AUTHORITY

Poura Bhawan, FD-415-A, Sector-III, Salt Lake, Kolkata - 700 106

e-mail: environmentwb@gmail.com

Wcb Portal: www.environmentwb.eov.in

No. 3488 /EN/T H 1/065/2015

Date: 2.64% May. 2016

M/s Deepesh Shoppers Pvt. Ltd.and others, 133, Canning Street, 2nd floor, Kolkata - 700 00!.

Sub: Provironmental clearance for the proposed residential complex at Mouza – Mankunda, Premises no. 55, Khan Road, P.O. & PS - Bhadreswar Municipality - Bhadreswar, Dist, Hooghly, West Itengal.

Sir.

This has a reference to your application for environmental elearance dated 07.09.2015 for the proposed residential complex at Mouza - Mankundu, Premises no. 55, Khan Road, P.O. & PS Bhadreswar, Dist. Hooghly, West Bengal and presentation made by you before SEAC on 01.10.2015.

Based on your application for environmental clearance and presentation made by you, SEAC in its meeting dated 29.03.2016 has recommended a list of stipulated conditions for the project proposal.

In addition to the SEAC's observations, it has been decided by SEIAA in the meeting dated 20.05,2016 that the following issues are to be addressed appropriately while submitting sauctioned hadding plan for obtaining environmental elegrance.

- Water meter to be installed at every inlet point of fresh water uptake. STP inlet & outlet including discharge point of treated water and regular records to be maintained.
- 2 Dedicated ear washing area to be earmarked and car washing water to be collected and treated in STP as proposed.
- Provision for backup power for operation of STP during power failure should be made.
- 4. Fraction of covered area that can be illuminated by natural lighting to be maximized and reported. Building should be oriented for maximum natural ventilation and day lighting.
- 5. Microclimatic studies to be completed as per the indicative guidelines for high-rise building.
- At least 40 KW of solar power to be generated and utilized in addition to the stand alone. solar street lights.
- and floor levels. Fire escape, evacuation proposal and means thereof, the refuge areas in the building plan to be submitted.

You are requested to prepare the construction plan incorporating those conditions before submission of the same for building plan approval. The sanctioned building plan may kindly be submitted in the secretarias of SEAC at Paribesh Bhayan, Salt Lake. The SEIAA shall consider the case only when it is ensured that the conditions listed in the enclosure have been properly addressed in the building plan.

Member Secretary, SEIAA May, 2016

No. 44837EN/T = H = 1/065/2015

Date: 26th

Copy forwarded for information to the Sceretary, State Level Expert Appraisal Committee.

Sd/-Member Secretary, SEIAA



Relegant parts of the Minutes of the 120th SEAC Meeting for stipulating conditions for environmental clearance of proposed Residential Complex by M/s. Deepesh Shoppers Pvt. Ltd. & Others at Monza-Mankundu, premises no-55, Khan mad, P.O & P.S-Bhadreswar, Dist-Hooghly, Name of the Environmental Consultant: M/s. Partho pratim Dutta.

This has reference to the application for environmental clearance dated 17.09,2015 and refers to your letter

dated 01,03,2016.

1 This is a proposal for construction of residential complex consisting of 21 residential buildings/18x3-6 storied & 3xG+7 storied) along with club & community facilities and total ross of flats 1124 nes.

7. The above proposal has been considered in the 110th SEAC meeting held on 01.10.2015 and 120th SEAC meeting held on 29.03.2016

3. Salient features of the proposed project are as follows: -

Land Area	37200.76 sq.m
Latitude & Longitude	22°50'47.9"N & 88°20'40"E
Expected Population	5083 (residents 4530, lemporary 553) person
Total Water requirement	691 XLD
Fresh Water requirement	461 KLD (municipal supply)
Wastewater generated	553 KLD (to be treated in STP)
Treated Wastewater reused	331 KLO (to be used in dual plumbing, landscaping & road woshing
Treated Wastowater discharged	167 KLD (to municipality drain)
Solid waste disposal	2.09 TPD (to be disposed off through as site compost plant δ -Bhadreswar municipality)
Total Huilt op Area	95601.719 sq.m (Phase 1 18902.052 sq.m)
Ground Coverage	11441.561 sq.m (30.756% of land area)
Total paved area	9244,509 sq.m (24,85% of land area)
Exclusive tree plantation area	7443.72sq.m (20.09% of land area)
Service area	1026,18 sq.m (2,759% of land area)
Water body area	1707.774 sq.m (4.591% of land area)
Gifted area to municipality	3!0.0 sq.m (0.83% of land area)
Other green area	6027.00 sq.m (16.20% of land area)
Plantation proposed	550 nos. (existing-25 nos. to be retained)
No. of Parking Spaces proposed	613 nos (open-388, covered-225).
Intal Power requirement	4066 KW (At least 40 KW of solar power to be generated)
Solar street light proposed	27 nos.
Backup Power	DG sets-3x386 KVA

^{4.} The State Level Expert Appraisal Committee, West Bengul, bereby, proposes the stipulated conditions for environmental clearance as per the provision of Environmental Impact Assessment Notification 2006 and the subsequent amendments, on the basis of above mentioned features along with other details submitted to SEIAA, subject to strict compliance of the terms and conditions (whichever applicable at building sanction stage) mentioned below.



Relevant parts of the Minutes of the 120th SFAC Meeting for slipulating conditions for environmental clearance of proposed Residential Complex by M/s, Despesh Shoppers P#t, Ltd. & Others at Mouza-Mankundu, premises no-55, Khan road, P.O & P.S-Bhadreswar, Dist-Hooghly, Name of the Environmental Consultant: M/s. Partho pratim Dutta.

Part A - SPECIFIC CONDITIONS

I. Construction Phase

Facility of labourers during construction: -

i. Provision of drinking water, wastewater disposal and solid waste management should be ensured for labour comps. Water usage during construction should be optimized to avoid any wastage.

ii. Proper sanitation facilities should be provided for construction workers to ensure environmental sanitation. Sewage generated from the areas occupied by the construction labourers have to be directed into the existing sewage drain of the area. In case of non availability of the sewer system, an ansite treatment system has to be provided.

10. The scaffolds, stears and platforms for construction works and the workers must be secured as far as

possible to prevent any accident.

iv. Health and safety of the workers should be ensured during construction. Personnel protective equipment like shoes, helmets, earmuffs, earplugs etc. should be provided to the workers. For vibration control damped tools must be used and the number of hours that a worker uses them must be limited. The Management must ensure that the workers put them white doing work that needs such protection, if any.

Rest and convenience shelter for workers with creche facility, if required, particularly for women, must

be provided with proper toilet facilities.

Steps to avoid disturbance during construction:-

All the tripsoil excavated during construction activities should be under cover/stored by relaining walls for use in horticulture / landscape development within the project site. Adequate erosion and sediment

control measures to be adopted before ensuing construction activities.

iii. Prior permission should be obtained from the competent authority for demolition of the existing structure, if any. Waste recycling plans should be developed for prior to beginning of demolition and construction activity. The plans should identify wastes in he generated and designate handling, recycling and disposal method to be followed.

iii. Disposal of muck including excavated material during construction phase should not create any adverse effects on the neighbouring communities and disposed off taking the necessary precautions

for general safety and health aspects.

iv. Diesel generator sets during construction phase should have accustic enclosures and should conform.

to E(P) Bules prescribed for air and noise emission standards.

v. Vehicles / equipment deployed during construction phase should be in good condition and should conform to applicable air and noise emission standards and should be operated only during nonneaking hours.

vi. Ambient noise levels should conform to residential standards both during day and night. Fortnightly monitoring of ambient air quality (SPM, SO2 and NOx) and equivalent noise levels should be ensured

during construction phase.

vii. Construction spoils including oituminous material and other hazardous materials including oil from construction equipments must not be allowed to contaminate watercourses and the dump sites for such material must be secured so that they should not leach into the ground water. If necessary, on trap should be installed where there is deployment of heavy machinerics.

vin Regular supervision of the above and other measures should be in place all through the construction phase so as to avoid disturbance to the surroundings. Discomfort in the neighbourhood due to the

proposed project activity should be minimized as far as practicable.

ix. Londing and unloading operations should not be carried out in open areas and should be preferably done during day time, if there is any major settlement in the surrounding areas. The construction activities including Piling work, Operation of Ready Mix Plant and Vibrator etc. should not be carried out during the might time (10 P.M. to 6 A.M.). Only essential operations, if any, may be carried out for a limited period during nighttime.

x. The proponent must ensure that no driven piles shall be proposed for this project, if there is any major

settlement in the surrounding areas.

 1.5m screen and adequate sprinkler arrangement shall be provided. Care should be taken to keep all. material storages adequately covered and contained so that they are not exposed to winds.

xii. Use of Ready-Mix concrete is recommended for this project.

xiii. Adequate measures to be adopted to avoid wastage of water for curing of concrete structures.

xiv. Adequate mitigative measures should be adopted to control dust emissions, noise and vibrations from construction activities. Vehicles and construction machineries should be properly maintained. Vehicles should conform to Pollution under control (PUC) norms.

Relevant parts of the Minnius of the 120° SFAC Meeting for stipulating conditions for environmental clearance of proposed Residential Complex by M/s. Deepesh Shoppers Pvt. 144. & Others at Mouzi-Mackundu, premises no-35, Khan road, P.O & P.S-Bhadreswar, Dist Houghly, Name of the Environmental Consultant: M/s, Parthe pratim Dutts.

xv. Look y available materials with less transportation cost should be used preferably.

xvi. Promotion of use of cleaner fuel and fuel quelity improvement should be come. I suggested energy consumption and fuel usage should be avoided.

wij Accomplation / stagnation of water should be avoided to ensure vector control.

Selection of materials for better energy efficiency:-

- Use of energy efficient construction materials should be ensured to achieve the desired thereo, comfort.
- Design layout should easure adequate solar access and ventilation. Proper planning and wholew design for daylight integration should be considered.
- III. Fly Ash is to be used for construction as per Notification No. S.O. 763(E) dated 14.09.1989 amonog vide Notification No. S.O. 979(E) dated 27.0.2003 and S.O. 2804(E) dated 03.11.2009 of the Ministry of Environment & Forests, Covt. of India.
- iv. Construction should conform to the requirements of local seismic regulations. The project proper ext should obtain permission for the plans and designs including structural design, support and specifications from concerned authority.
- Construction technologies that require less material and possess high strength should be adopted.
 Materials with low embodied energy and high strength should be used preferably.
- The building will be constructed and provisioned to use natural sunlight to the maximum during the day time, during use.
- vii. Use of afternate building materials and alternate construction techniques should be considered apart from the conventional materials and methods. Use of bullow unit masonry should be considered.
- viii). Use of energy efficient lighting systems e.g. High Pressure Sodium Vapour (HPSV) temps, LED etc. should be premoted. Solar energy should be used for coldeer lighting. Adequate no. of solar lights should be installed for external lighting as per norms. All common area lighting will be LED system.
- ix. Solar water beating arrangement will be done for water heating ,
- *. Passive solar cooling to be incorporated in building design. Buildings should be criented for ensuring natural ventilation and daylighting.
- xo. Proper insulation of roof should be provided to achieve desired thermal comfort. Use of light coloured, reflective roofs having an SRI (solar reflectance index) of 50% or more should be incorporated.
- xi. Use of high albede or reflective pavenients to keep parking lots, pavements and inside roads and should be incorporated.
- xiii. Guidelines to the occupants should include usage efficiency measures such as energy efficient lighting and water efficient system.
- paved surfaces to minimize beat island effect and imperviousness of the site.
- av. Adequate open space, greenery and water boiles to be provided as per rules.
- xvi. Any proposed building with air-conditioning facility should follow the norms proposed in the ECBC regulations framed by the Bureau of Energy Efficiency, Use of chillers will be CFC & HCFC free.

avii. Restrict the use of glazed surface as per National Building Code 2005.

Water Body Conservation:-

Water body of area 1707.774 sq.m should not be lined and their embankments should not be cameried. The water body is to be kept in natural conditions without disturbing the ecological module. The see & location of the water hodies in he shows to the building plan sanctioned by the concerned municipally.

Plantation Proposal:-

- 1 The unit should strictly abde by The West Bengal Trees (Protection and Conservation in Non-Energy Areas) Rules, 2007. The proponent should undertake plantation of trees over a literal 20% of the total area.
- ii. No tree can be felled without prior permission from the Tree Cutting Authority constituted as per the West Bongal Trees (Protection and Conservation in Non-Ecrest Areas) Act, 2006 and subsequent rules.
- iii. The proposent should also, at least 525 nos, of trees as proposed in addition to the existing trees to be retained. The landscape planning should include plantation of native species. The species with heavy foliage, brook leaves and wide canopy cover are desirable. Weter intensive uneder invosive species should not be used for an escaping.
- iv. Provision for Roof Top Gardening is mandatory.

Water supply:-

Water requirement during construction phase shall be met from municipal supply. Crosso water should not be abstracted with out prior permission obtained from the competent authority as per the West Benga, Graynd Water Resources (Management, Control and Regulation) Act, 2005.

Low

Socretary, State Expert Approxisal Committee, West Benge

87

Relevant parts of the Minutes of the 120° SEAC Meeting for stipulating conditions for environmental clearance of proposed Residential Complex by M/s. Deepesh Shoppers Pyt. 1td. & Others at Mouza-Mankundu, premises no-55, Khan road, F.O & P.S-Bhadreswar, Dist-Hooghly. Name of the Environmental Consultant: M/s. Partho pratim Datta.

Sewage Treatment Plant:-

As per the proposal submitted by the proponent waste water shad be treated in soptic tank to soak pit.
 Construction waste water to be collected in sedimentation trap with adequate retention time and to be reused.

Storm water Management & Miligation of Heat Island Effect:-

- Imperviousness of the site shall not exceed the NBC (National Building Code 2005) standards for imperviousness factor applicable to different types of area.
- Total paved area of site under parking, mads, paths or any other use should not exceed 25% of the site area.

 Minimum 50% of paved area on site should have pervious paving or shaded under vegetation or topped with fluish boving solar reflectance of 0.5 or higher.

iv. Adequate storm water drainage network to be designed for the project without disturbing the surrounding settlements. Storm water management plan should be implemented so as to prevent sudden discharge of excessive volumes of storm water to the receiving waters thus reducing the shock had on the drainage system and impact on receiving water body.

v. Disruption to the natural hydrology of the site should be minimised by reducing impervious cover, increasing on site infiltration and managing storm water run off.

vi. Heat island effect should be minimized by use of shading or reflective surfaces, mainly the surfaces that contribute to the heat island effect i.e. streets, sidewalks, parking lots and buildings. White roofs should be provided in the buildings.

Rain Water Harvesting Scheme:-

- The proposent must follow the Rainwater Harvesting Guidelines of the State Expert Appraisal Committee (SEAC) available in the website (http://www.wbpcb.gov.ip).
- The proponent must collect rainwater from roof-top catchments and reuse for various purposes after necessary cleaning. Adequate retention time and storage provisions should be provided for howesting rainwater.
- iii. Adequate firefighting storage should be provided as per norms.

Municipal Solid Waste Management :-

 Adequate provision shall be made for storage and segregation of solid waste and adequate means of access shall be provided.

Transport Management: -

- Both internal and external traffic planning and management should be adequate to ensure numberrupted traffic provement in the area during construction as well as operation phase.
- ii. The design of service road and the entry and exit from the project area should conform to the norms & standards of competent authority for traffic management. But mouth type arrangement should be made at the entry & exit. Proper traffic management plan should be adopted in consultation with Traffic authorities.
- Clarified Wastewater will be used for sprinkling water on the unpaved internal roads on a regular basis.

Others

- All wandstory approvals and permission as required from Director of Explosives, Fire Department etc. should be obtained.
- Provision of Effective Controls and Building Management Systems such as Automatic Fire Alarm and Fire Detection and Suppression System etc. must be ensured.

iii. Efficient management of indoor air quality must be ensured for health and safety of the users.

- iv. Adequate measures to be adopted for water conservation during construction and operation stage. Use of efficient irrigation equipment, evaporative cooling unit in air-conditioning system etc should be considered.
- v. Rost room facilities should be provided for service population.
- vi. Adequate access to fire tenders should be provided.

Suis/

Relevant parts of the Minutes of the 120° SEAC Meeting for stipolating conditions for environmental clearance of proposed Residential Complex by M/s. Deepesh Shoppers Pvt. 14d. & Others of Monza-Mankandu, premises no-55, Khan road, P.O.S. P.S-Bhadreswar, Dist-Hooghly. Name of the Environmental Consultant: M/s. Partho pratica Dulla.

II Operation Phase

Water supply :-

 Water requirement during construction phase shall be mot from ground water. Cround water should be abstracted as per prior partrission obtained from the competent authority as get the West Burgo; Ground Water Resources (Management, Control and Regulation) Act, 2005.

ii. Arsene removal plant to be installed at ground water source.

ii. Use of water meter conforming to ISO standards should be installed at the lotet point of water optake to monitor the daily water consumption. Use of water efficient devices / fixtures and appliances should be promoted. Installation of dual flushing system should be considered in conserve water.

The proponent must practice relowater baryesting on regular basis.

Sewage Treatment Plants-

7. As per the proposal submitted by the proponent, waste water shall be treated in STP. Freated waste water shall be parily reused for dual plumbing, landscaping; substant read and pavement cleaning etc. and rest will be discharged to municipal drain.

ii. Reuse of trouted wastewater should be carried out as proposed.

in. Back up power for operation of STP should be kept during power failure.

Emission from Diesel Cenerator Set: -

 Noise barriers will be provided at appropriate locations so as to ensure that the noise levels do not exceed the prescribed standards. Diesel generator sets about be provided with integral according enclosure at the manufacturing stage itself as per CPCB norms.

The stack height and emissions from D.G. sets should conform to the norms of Central Pollution Control Board. The certification of space design for DG sets should be done by computed authority.

Ensure Energy Efficiency:-

i. Use of energy efficient construction materials to achieve the desired thermal confort should be incorporated. The desired level of R and U factors must be achieved. U factor for the top mof should not exceed 0.4 Watt/sc,m/degree configurate with appropriate modifications of specifications are hudding technologies. The provisions of National Building Code 2005 should be strictly followed.

ii. Use of energy efficient electrical systems should be premoted. High efficiency lamps with electronic

hallasts should be used.

- iii. Buergy efficient Motors and properly rated Transformers should be installed. Manufacturer's contribate to this effect shall be obtained and kept on record. Back up power supply should be basen on cleaner fuel.
- iv. The power cabling shall be adequately sized as to maintain the distribution losses not to exceed 1% of the total power usage. Record of transmission losses shall be maintained. The proponent shall install permanent electrical matering to record command (kVAL energy (kWh) and total power factor.

Transport Management: -

Use of public mode of transportation should be promoted. Use of the least polluting type of transportation should be promoted. Adequate parking space should be provided as per norms.

The Pathways should be covered or shadowed by tree carepy as far as practicable. Fransport system should be such that traffin will be calm in neighbourhoods. Traffic within the project site should be restricted by regulation. Adequate vertical and horizontal clearances of overhead electric power and telegramentication lines should be provided.

Solid Waste Management:-

The proponent should abide by the Municipal Solid Wostes (Management and Handling) Rules, 2000.
The proposent must develop the Solid Waste Management and Disposal Scheme ensuring sharage and segregation of biodegradable and consideration wastes. The solid waste is to be disposed off in consultation with concerned at themity.

ii. The proposent shall install ensite compost plant for treatment of biodegradable part of Musicipal Sould-Waste. Sufficient space for installation of onsite compost plant, should be provided and operation of the compost plant considering full occupancy of the operationals i.e. the capacity of garbage ciscosal unit.

shop dihe selected encomingly.

(ii) The handling agency should also take care of the recyclable wastes like plastic, paper board, glass etc. and also ment materials to case of respective municipal authorates want to avoid any kind of waste, from the bousing complex.

Secretory, State Kypert Appraisal Committee, West Rengal

Page 5 of 7

Relevant parts of the Minutes of the 120° SEAC Meeting for stipulating conditions for environmental clearance of proposed Residential Complex by M/s. Deepesh Shoppers P&L Ltd. & Others at Menza-Mankundu, premises no-55, Khan road, P.O & P.S-Bhadreswar, Dist-Hooghly. Name of the Environmental Consultant: M/s. Partho pratim Dutta.

- iv. The proponent should have sufficient area for horticulture where the compost generated can be used as tertilizer and soil supplement and also have arrangement for sale of excess quantity of compost.
- v. Provision for treatment of leachate generated and odor control in onsite compost plant should be made.
- vi. Non-recyclable inorganics and rejects will be disposed off through municipal authority as proposed.
- vii. The proposent should provide different coloured bins for different categories of waste and ensure complete segregation of blodegredable and non-biodegradable wastes. The solid waste from different collection and storage bins should be finally collected at transfer stations. Further segregation will be done at transfer stations to collect recyclables such as plastic, polythene, glass, metals, textiles, rubbers, leathers, paper etc. Separate compartments shall be provided for each type of recyclables.
- viii The proponent should abide by the Hazardous Wastes (Management, Handling and Transboundary Movement) Rules, 2008. Collection and storage of hazardous wastes during Pre-construction and Post construction activity should be planned properly. The expected hazardous wastes should be disposed off separately as per the Hazardous Wastes (Management, Handling and Transboundary Movement) Rules, 2008.
- ix. Spent oil from DG Sets should be stored in HDPE drams in isolated covered facility and disposed off as per the Hazardous Wastes (Management, Handling and Transboundary Movement) Rules, 2008. Spent oil from DG Sets should be disposed off through registered recyclers only.

Others :-

- The implementation of Environmental Management Plan should be carried out, as proposed. Regular monitoring should be carried out during construction and operation phases.
- ii. The project proponent should provide guidelines to the users to ensure conservation of energy and water. In-house environmental awareness campaigns should be carried out at regular intervals to ensure environmental protection.
- Fire tighting systems should be designed in compliance with the WBPS and NBC norms. Preventive measures should be adopted for Risk & Disaster Management as per the provisions of the National Building Code 2005.
- iv. The Corporate Social Responsibility Plan with specific financial commitment should be implemented for the proposed project. At least 2% of the total project cost should be utilized for Corporate Social Responsibility programmes.
- The proposest should abide by the Direction issued by the Department of Environment, Government of West Bengal, vide No. EN/3170/T-IV-7/001/2009 dated 10.12.2009.
- vi. Environmental Mecagement Information System shall be maintained properly.
- vii. The proposent should restrict the use of glazed surface as per National Building Code, 2005.
- viii. All the recommendation made in the EMP report should be compiled with.

Part B GENERAL CONDITIONS

- The environmental safeguards contained in the EMP Report should be implemented.
- All the conditions, liabilities and legal provisions contained in the Stipulated conditions for Environmental Cicarance (SCEC) shall be equally applicable to the successor management of the project in the event of the project proponent transferring the ownership, maintenance of management of the project to any other entity.
- 3 All the labourers to be engaged for construction works should be screened for health and adequately treated before issue of work permits. Provision should be made for the supply of keroseae or cooking gas to the labourers during construction phase.
- The project proponent should make financial provision in the total budget of the project for implementation of the suggested safeguard measures.
- 5 In case of any violation of the conditions laid down in this SCEC, Section 16 of The Environment (Protection) Act, 1986, will be applicable. In case of any change(s) in the scope of the project, the project would require a fresh appraisal by the SEAC, West Bengal.
- 5. The Stote Expert Appraisal Committee, West Bengal reserves the right to add additional salequard measures subsequently, if found necessary, and to take action including revoking of the stipulated conditions for environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested salequard measures in a time-bound and satisfactory manner.
- 7. All other statutory degrances such as the approvals for storage of diesel from Chief Controller of Evolutives, Civi Aviation Department (if required) etc. shell be obtained by project proponents from the competent authorities.

LY

Relevant parts of the Minutes of the 120° SEAC Meeting for stipulating conditions for environmental clearance of proposed Residential Conquex by M/s. Deepesh Shoppers Pvt. 1.td. & Others at Meeza-Mackundu, premises no 55, Klisa a.sd. P.C & P.S-Bhadressar, Dist-Hoogbly. Name of the Environmental Consultant: M/s. Partho pratim Dults.

8. Provision for incorporation of appropriate conditions in the Sale Agreement / Dead, for ensuring sustained Operation and Maintenance (O&M) of the common laddities (STP, Ratiovator Egyposting system, Solid waste management system, Solar street lights etc.) even after transfer of newforship of

the project, should be made in explicit and transparent manner.

 These appointments would be unforced among others under the provisions of the Water (Provention & Control of Pollution) Act, 1974, the Air (Provention and Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Neitheation

2006 including the amendments and clarification circulars.

10. The final Environmental Clearance shall be accorded by the State Environmental trapact Assessment Authority. West Bengal after submission of master site plan of the whole protect senctioned by the concerned municipality incorporating all the satisful features of the stipulated conditions for environmental clearance and necessary documents and consideration of the satisful by the State Level Expert Appraisal Committee, West Bengal. The area statement as well as detailed building profile, parking spaces etc., as proposed in the satisful features, should be clearly mentioned in the sonctioned Master Plan.

Ne

Secretary

State Expert Appraisal Committee, West Bengal

(Prof. S Neoga) Chairman

State Expert Appraisal Committee, West Bongal