




Scanned by CamScanner



Scanned by CamScanner





CERTIFIED COPY

Before starting any Construction the site must conform with the plans sanctioned and all theconditions as proposed in the plan should be fulfilled.

The validity of the written permission to execute the work is subject to the above cenditions

Non Commencement of Erection Re-Erection within Two Year will Require Fresh Application for Sanction.



Design of all Structural Members including that of the foundation should conform te Standards specified in the National Building Code of India

No rain water pipe should be fi ed.or discharged on Road or Footpath, Drainage plan should be submitted at the Borough Executive Engineer's Office and the sanction obtained before proceeding with the drainage work.

A suitable pump has to be provided i.e. ng unfiltered water for the distribution to the flushing cisterns and urinals in the building incase unfiltered water from street main is not available

DEVIATION WOULD MEAN DEMOLITION

RESIDENTIAL BUILDING

CONSTRUCTION SITE SHALL BE MAINTAINED TO PREVENT MOSQUITO BREEDING AS REQUIRED U/S 496 (1) & (2) OF CMC ACT 1980. IN SUCH MANNER SO THAT ALL WATER COLLECTION & PARTICULARLY LIFT WELLS, VATS, BASEMENT CURING SITES, OPEN RECEPTACLES ETC. MUST BE EMPITED COMPLETELY TWICE AWEEK.

fram Ou 100 - 201940087

The building materials that will be stacked on Road/Passage or Foot-path beyond 3-months or after construction of G. Floor, whichever is earlier may be seized forthwith by the K.M.C. at the cost and risk of the ewner.

Plan for Water Supply arrangement including SEMILI G. & O. H. reservoirs should be submitted at the Office of the Ex-Engineer Water Supply and the sanction obtained before proceeding with the work of Water Supply any deviation may lead to disconnection/demolition.

res need to be taken for pollution free

- 2) A sp construction area/buildings with geotestile fabric installing dust barriers, or other actions, as appropriate for the location,
 3) depty write and maintains solds in a visible damp or crusted condition for temporary stabilization.
 4) Reply write rand maintains solds in a visible damp or crusted condition for temporary stabilization.
 5) Reply write prior to lecking or any other earth moving activity to keep the soil moist throughout the process.
 4) The stabilization of the process of the
- The rate of the sent distorbed soils following paying activities with inmediate landscaping activity or including only proposed or rock cover. Manate indust control during working hours and clean track out from paved surfaces at the end of the out and/day. Track our must now extend 50 feet or more and must be cleaned daily, at the

- the dispersion of the state of

| 13 to Clean and debts indecline anticly
| 15 per anticle and the exhibition to most light speed within the work site.
| 15 to Clean accretises shift by repose exists control/holde control facility.
| 15 per 15 per accretises shift by repose exists control/holde control facility.
| 15 per 15 per accretises shift by repose exists the state of the state



KOLKATA MUNICIPAL CORPORATION

Borough No...

S. Mushy

Assistant Engineer K

CERTIFIED COPY OF B.S. PLAN

BUILDING DEPARTMENTS

Am

Executive Engin