

Plan for Water Supply arrangement including SEMILI G. & O. H. reservoirs should be submitted at the Office of the Ex-Engineer Water Supply and the sanction obtained before proceeding with the work of Water Supply any deviation may lead to disconnection/demolition.


A suitable pump has to be provided i.e. pumping unfiltered water for the distribution to the flushing cisterns and urinals in the building incase unfiltered water from street main is not available.

No rain water pipe should be fixed c discharged on Road or Footpath. Drainage plan should be submitted at the Borough Executive Engineer's Office and the sanction obtained before proceeding with the drainage wor

Necessary steps should be taken for the safety of the lives of the adjoining public and private properties during construction.

DEVIATION WOULD MEAN DEMOLITION

THE SANCTION IS VALIED UP TO 16 02 2023



The building materials that will be stacked on Road/Passage or Foot-path beyond 3-months or after construction of G. Floor, whichever is earlier may be seized forthwith by the K.M.C. at the cost and risk of the owner.

CONSTRUCTION SITE SHALL BE MAINTAINED TO PREVENT MOSQUITO BREEDING AS REQUIRED U/S 496 (1) & (2) OF CMC ACT 1980. IN SUCH MANNER SO THAT ALL WATER COLLECTION & PARTICULARLY LIFT WELLS, VATS, BASEMENT CURING SITES, OPEN RECEPTACLES ETC. MUST BE EMPITED COMPLETELY TWICE A WEEK.

> All Building Materials to necessary & construction should conform's to standered specified in the National Building Code of India.

Non Commencement of Erection/ Re-Erection within Two Year will Require Fresh Application for Sanction

Sanctioned subject to demolition of existing structure to provide open space as per plan before construction is started

Executive Engineer (C)

Ass Asst. Engineer (C) Br. PLAN VILL

Approved By: MBC Meating No. 539 Item No. 162/17-18 Dt. 15 09 2013

GREEN BUILDING

Green Building Rating. Incample Gold.

Certifying Authority. IG.BC...

Reference No.G.H. 17-2135



RESIDENTIAL BUILDING

GOVERNMENT OF WEST BENGAL Office of the Director General West Bengal Fire & Emergency Services 13-D, Mirza Galib Street, Kalkata – 700 016.

OFFICE OF THE EX-ENGINEER (CIVIL)
BUILDING DEPARTMENT BOROUGH-VIII Dane 30.08-17-THE KOLKATA MUNICIPAL CORPORATION 104, RASH BEHARI AVENUE

KOLKATA-700 029

Mono. No - WBFES 1677-4 / 17/ Kol-RBC/124/17(124/17) teem : Divisional Fire Officer Fire Prevention Wing West Bengal Fire & Emergency Services. Busant Kumar Papakh, Authorised Representative o Ganges Estate Pet, Litt., 1, Garstin Place, Kolkata - 700 001.

Sub : Fire Safety Reconsecutation for Proposed Construction of B+G+XV Storicd Wing 2 & G-HI Storicd Wing 1 Under Group Residential Building at the Premises No. 1, Lower Rowdon Street, Ward No. 69, Borough No. VIII, Kolknia-700 020. Write Construction prea/fundishings with geotextile fabric installing dust barriers, or other actions, as impropriate for the hecation.

A substructor and maintain soils in a visible damp or crusted condition for temporary stabilization.

An activity are raise to be eling or any other earth moving activity to keep the sail moist throughout the

This is in reference to year Letter No. Nil, Dated, 27.02.2017, Regarding Fire Sufety Measure Proposed Construction of H1G/XV Storied Wing 2 & Grill Storied Wing 1 Under Group Residential, Building at the Premises No. 1, Lewer Royston Street, Ward No.-59, Bornigh No.-VIII, Kelkata-790 020. The plan submitted by you was sentitized and marked as found necessary from fire safety point of view in returning one set of plan with recommendation, this office is issuing Fire Safety Recommendation, in favour of the after-said building subject to the compliance of the following fire safety measure. However, necessary sunction and approval for such construction and occupancy must be obtained from competent

Englises

ARVIND KUMAR NEOTIA

manufulli.

Stabilize identify surfaces using soll-winders until vegetation or ground cover can effectively stabilize the free.

Stabilized of details in consultation with the local authorities fullowing proper environmental

limit within speeds to 15 mph on the work site.

in English seas without proper dust control/holse control facility.

The season was a subject proper dust control/holse control facility.

The season was a subject without effective cover.

The season was in this work area except workers to burst soil disturbance and prevent access by refuse average of the period of the subtable barrier.

This proper proper price, being of the subtable barrier.

ार्षि हिंदु भाग etilat; di debits en thé inadsine pavements. पर्याद्वीय क्षेत्र पर्यंत्र कि hat intendentiac à tuel derine construction audrepair of the wads for meltone कुर्तु के कुर्वे के क्षा added:

Chengabash and undercarriage of faul tricks prior to leaving construction site.

Applicand maintain dust suppressant on had rouges,

Applicand maintain dust suppressant on had rouges,

Applicand maintain dust suppressant site of his process of the stockpiles at completion of activity by water and

maintain a dust nathritive to all outer surfaces of the stockpiles at completion of activity by water and

maintain a dust nathritive follower surfaces of the stockpiles.

Statistics surface soils where loaders, support equipment and vehicles will operate by using water and

maintain surface soils in a statistical condition where loaders, support equipment and vehicles will

presented.

Georges: Stability adjacent disturbed soft following paving activities with immediate landscaping activity or instifying on vinctuities or reck copyr.

It aligns dust control during working hours and clean track out from paved surfaces at the end of the years fill tally. Track out must now extend 50 feet or more and must be cleaned daily, at the