ANNEXURE: X

SCHEDULE OF WORK (SPECIFICATION OF THE CONSTRUCTION)

STRUCTURE: R.C.C. Foundation with R.C.C. framed structure with R.C.C. Roof all confirming to N.B.R. As per plan Brick works

OUTER WALL: 8 inches with both side plaster.

INNER PARTION WALL:5 inches or 3 inches to be plastered both side as usually done.

INSIDE WALLS OF FLATS: Shall be finished with plaster of paris. All inside floors shall be casted polished with white marble flooring, with skirting approx with white cement.

MAIN DOOR:

Frame: 4" x 2.5" made of sal Wood or equivalent. Pallah: 32 mm phenol bounded water flush door.

BED ROOM DOORS (FACING DRAWING ROOM) -

Frame: 4" x2.5" made of sal Wood or equivalent Pallah: 32 mm phenol bounded water proof flush door.

BALCONY KITCHEN DOCKS:

Frame: 4" x2.5" made of sal Wood or equivalent Pallah: 32 mm phenol bounded water proof flush door

BATHROOM DOORS:

Frame: Made of P.V.C.

Pallah: P.V.C. or equivalent and of suitable colour of Developer choice.

ELECTRICAL;

ConceledFinolex/habelles with copper wiring as under

Drawing Room: Two Light point, two Fan point, one plug point, Bed Room: Two Light point, one Fan point, one plug point, Kitchen: One light point, one exhaust point, one power plug point, Bathroom - One light point, one exhaust, one gizer point.

SANITARY FITTINGS:

Bussin/Commode/white and reputed make (1No.)
Tup & other Fittings: Essco Omco or equivalent.
Tiles upto 6ft high in bathrooms. Exhaust fan point.

GENERAL BATHROOM:

Tap: 2 Nos.

Shower: I No. Indian Commode with PVC cistern-white.

Arrangement for hot &Cold water

WINDOWS:

Aluminum sliding window fitted with glass.

KITCHEN:

Cooking Platform: Granite Stone and upto 3 ft. high glazed tiles fittings over the black granite stone, exhaust fan point.

Tap: 2No; Sink: Steel.

Boundary Wall :Brick wall upto to 5ft height. Side Space :casted and finished with net cement.

Lift :Lift to be installed.

NS CONSTRUCTION

Niloy Prolish Gauge

NS CONSTRUCTION

Author

Partner