



STRUCTURAL CERTIFICATE
 THE STRUCTURAL DESIGN AND DRAWING OF BOTH FOUNDATION AND SUPERSTRUCTURE HAS BEEN CHECKED AND FOUND TO BE IN ACCORDANCE WITH THE BUILDING CODE OF INDIA, AND CERTIFIED THAT IT IS SAFE AND STABLE IN ALL RESPECT.

DECLARATION OF E.R.A.
 I, **SURESH CHANDRA SARKAL**, R.C.E. A. M. L. STRUCT. E. W. No. 100001010, Registered Professional Engineer, RAJASTHAN PROFESSIONAL ENGINEERS ASSOCIATION, RAJASTHAN, INDIA, DO NOT UNDERTAKE ANY RESPONSIBILITY FOR THE DESIGN AND DRAWING OF THE STRUCTURE OF THE BUILDING AND THAT IT IS A BUILDABLE SITE AND NOT A HAZARDOUS WILDLIFE SITE.

OWNER'S NAME: AGNI DELCOM PVT. LTD. & OTHERS
PROJECT: REVISED G+IV STORED RESIDENTIAL BUILDINGS AT HOLDING NO. 14, DHARMAMATA ROAD, L.R. KHATAN, NOS. 4636-4641, R.S. KHATAN NO. 726, 992, 194, 276, 222, 218, R.S. DAG NO. 1399, 1376, 1385, 1384, 1376, 1382, 1379, 1380, 1383, 1381, P.S. SONARDEVA, M.O. 22, KODALI, RAJASTHAN, INDIA. MUNICIPALITY SANC. PLAN NO. 1330, CB 22/2/26, DATED 21.11.2014.

APPROVED BY: Sanyalson Associates Consultant Pvt. Ltd. CONSULTANT PLANNER & STRUCTURAL ENGINEERS
 DWG NO - 03/08 BLOCK - 1 SHEET CONTENT - TYPICAL FLOOR PLAN ROOF PLAN, SECTIONS & ELEVATIONS

DOOR & WINDOWS SCHEDULE

M/S	SIZE
W1	1500 X 150
W2	1200 X 150
W3	1000 X 100
W4	600 X 75
D1	1050 X 210
D2	900 X 210
D3	250 X 210

- NOTES**
1. ALL DIMENSIONS ARE IN MM.
 2. ALL EXTERNAL WALLS ARE 200 TH. AND INTERNAL WALLS ARE 100 TH. UNLESS OTHERWISE SPECIFIED.
 3. FOUNDATION BRICK WORK WILL BE 1ST CLASS.
 4. DEPTH OF SEPTIC TANK AND SEMI-LUGA WATER RESERVOIR WILL NOT EXCEED THE DEPTH OF BUILDING FOUNDATION AT THE TIME OF CONSTRUCTION.

- SPECIFICATIONS**
1. 7.5 TH. CLASS BRICKS IN FOUNDATION & FLOOR.
 2. 1:3 CEMENT SAND & KHAN CEMENT CONCRETE IN FOUNDATION & FLOOR.
 3. FOUNDATION BRICK WORK WILL BE 1ST CLASS.
 4. 12.5 TH. & 7.5 TH. PARTITION BRICK WORK WILL BE 1ST CLASS.
 5. EXTERNAL WALLS WILL BE 15 CEMENT MORTAR.
 6. 2.5 TH. D.P.C. WILL BE 1:2.4 WITH PROPER WATER STOPPING.
 7. R.C.C. CONCRETE WILL BE 1:2.4 CEMENT SAND & STONE CHIPS MATERIALS AND MIXING IN THEIR PROPER MANNER.
 8. FLOORING WILL BE 100 TH. WITH 10.25 MM. TH. F.L.S. FLOORING.
 9. CEILING AND ALL C.C. PLASTER WILL BE 12mm. TH. WITH 10.25 MM. TH. F.L.S. FLOORING.
 10. GRADE OF CONCRETE M - 20.
 11. ALL BUILDING MATERIALS WILL BE AS PER I.S. CODES.