SPECIFICATIONS

Component	Brand/ Specification	
STEEL	SAIL or similar make	
CEMENT	Lafarge, Ultratech, or similar make	
STRUCTURE	Proper foundation to be made as per drawing given by the structural engineer and architect	
BRICKWORK	External walls will be 8 to 10", Internal walls to be 5" thick after plastering	
TERMITE TREATMENT	Termite treatment to be provided	
FLOORING	Marble/ Tiles to be provided in the flooring of the flats	Non Skid tiles to be provided in th flooring of the bathroom and th kitchen
DOOR FRAMES	All to be of 4" x 2.5" Malaysian Sal	
DOORS	Internal doors will be 35mm thick with bronze hinges.	External doors will be solid tes
LOCKS	All locks will be Godrej or of similar make	panor 40010
WINDOWS	Windows to be of high gauge aluminum sliding with Saint Gobain or similar quality glass of 6mm thickness	
WALL (INSIDE)	To be covered with JK /Birla or similar putty	
WALL (TOILET)	Toilets to be covered with good quality branded ceramic tiles upto to door lintel level.	
WALL (OUTSIDE)	External acrylic paint of superior brand such as Asian/ Berger or similar brand. And stone or artificial cladding to be used for superior look.	
PLUMBING	All bathrooms to be fitted with Kohler or similar brand fixtures and fittings.	
WATER PROOFING	Adequate water proofing will be done in all toilets, roof, over head underground tank, lift pit and planters if any.	

ECOPRIME HIGHRISES PVT LTD

AUTHORISED SIGNATORY

ELECTRICAL SWITCHES\ MCB\ DB INTERCOM LIFT	Concealed wiring to be provided with ISI copper wire such as Finolex, Havells or similar make All to be Le Grande, Havells or similar make Intercom and CCTV's to be provided Kone, Otis, or similar make to be provided
FIRE FIGHTING	Adequate fire fighting arrangements will be there as per requirements of West Bengal State Fire Services.
GENERATOR	Generator to be provided
LIGHTING	Adequate lighting arrangements with decorative fittings to be provided at the gate, pathway and around the building for security.

ECOPRIME HIGHRISES PVT LTD

AUTHORISED SIGNATORY