

main is not available.

Plan for Water Supply arrangement including SEMILI G. & O. H. reservoirs should be submitted at the Office of the Ex-Engineer Water Supply and the sanction obtained before proceeding with the work of Water Supply any connection/demolition.

CONSTRUCTION SITE SHALL BE MAINTAINED TO PREVENT MOSQUITO BREEDING AS REQUIRED U/S 496 (1) & (2) OF CMC ACT 1980. IN SUCH MANNER SO THAT ALL WATER COLLECTION & PARTICULARLY LIFT WELLS, VATS, BASEMENT CURING SITES, OPEN RECEPTACLES ETC. MUST BE EMPITED COMPLETELY

TWICE A WEEK. Before starting any Construction the

site must conform with the plans sanctioned and all the conditions as proposed in the plan should be fulfilled. The validity of the written permission to execute the work is subject to the above conditions.

> Approved By : MPH 568 M.27/2 The Building Committee

Sanctioned By: Assistant Engineer (C-B) Br. No....

The sanction refers to the proposed portion shown in red and the Executive Engineers makes no admission as to the correctness of the plan.

Design of all Structural Members APPROVED including that of the foundation should conform to Standards specified in the National Building

All Building Materials to necessary & construction should conform's te standered specified in the National

Non Commencement of Erection/ Re-Erection within Five year will Require Fresh Application for Sanction

Code of India

Building Code of India.

DEVIATION WOULD WEAN DEMOLITION

RESIDENTIAL BUILDING

A suitable pump has to be provided i.e. pumping unfiltered water for the distribution to the flushing cisterns and urinals in the building incase unfiltered water from street

The building materials that will be stacked on Road/Passage or Foot-path beyond 3-months or after construction of G. Floor, whichever is earlier may be seized forthwith by the K.M.C. at the cost and risk of the owner.

KULKATA MUNICIPAL CORPOR BUILDING PERMIT Date 12/2/21 Borough No. Ex Engineer / Asst Engineer Br. No.... Ber No.... BUILDING DEPARTMENT

THE SANCTION IS VALIED

Any unathorised construction done in deviation from the Sanction Building permit and the Completion Plans after issuance of this Completion Plans may cause revocation of the Occupancy Certificate.

No rain water pipe should be fixed discharged on Road or Footpath. Drainage plan should be submitted at the Borough Executive Engineer's Office and the sanction obtained before proceeding with the drainage work

Necessary steps should be taken for the safety of the lives of the adjoining public and private properties during construction.



A. Preventive measures peed to be taken for pollution free environment:-Resolutions of MBC Meeting

MeetingNo 568 MeetingDate 27/02/2020 Total No of Cases: 22 a) Myrap construction area/buildings with geotextile fabric installing dust barriers, or other actions, as appropriate for the location, (b) Apply water and maintain soils in a visible damp or crusted condition for temporary stabilization. Apply water prior to leveling or any other earth moving activity to keep the soil moist throughout the Proposal:

Proposal:

This is a proposal for sanction of G+IV storied residential building of height 15.44 meter w's 393A of the KMC Act, 1980. Area of the plot is 4474.613 Sq.M. (physical) and width of the abutting road is 5.156 meter. Applicant proposed to gift 2.5 m width strip of land throughout the entire frontage to saval the advantage of height. Applicant took the advantage of excess ground coverage and car parking area as per provision of rule utr 70(4) and rule 69(g).

Name of Architect: Anithan Bhadhuri Mondal, CA/2003/31394

Name of GTE: Alok Roy, I/11

Name of GTE: Alok Roy, I/11

Name of Applicant: Anudeep Jhunjhumvala, Director, Anant Vincom Pvt. Ltd. & others

Total Proposed Gross Floor Area: 8790.79 Sq.M.

Exempted Area: 845.36 Sq.M.

NOC / Observation: UL(C&R) Act 1976 (no \$77/XVI/4031/2018-U.L. dated 23/02/2018) d) Limit winicle spends to 13 mph on the work site. a) Clean wheels and undercarriage of haul trucks prior to leaving construction site. f) Apply and maintain dust suppressant on haul routes. g) Apply a cover or screen to stockplies and stabilize stockplies at completion of activity by water and maintain a dust calliative to all order surfaces of the stockplies;

Resolution:

The matter was placed in \$67th MBC meeting dated 18/02/2020 vide item no 204/19-20 and was deferred for meedification of plan proposal regarding driveway, stair position and stair numbers. Now applicant submitted revised plan incorporating above observation. The revised plan proposal has been examined in the Building Committee in detail. Department has to check and update area statement on the basis of revised plan if required. The proposal is recommended for sanction subject to compliance of above and other departmental requisitions and departmental circulars, if any. There is no violation of rules, as such.

K.P. (TRAFFIC) W.B.F. & E.S.

Vant Inda

. W.B.P.C.B.

Signatures of Members

Office of the Members

Office of the Members

A K. P.

A K. P.

A K. P.

A C. Members

A Members

in). Stabilize surface soils where loaders, support equipment and vahicles will operate by using water and maintain surface soils in a stabilized condition where loaders, support equipment and vehicles will Operate.

Stabilize adjacent disturbed soils following paving activities with immediate landscaping activity or Installation of vegetative or rock cover. 1) Maintain do stontrol during working hours and clean track out from paved surfaces at the end of the work slet Track out must now extend 50 feet or more and must be cleaned dally, at the k) Stabilize sloping surfaces using soil binders until vegetation or ground cover can effectively stabilize. I) Disposal of debuts in consultation with the local authorities following proper environmental management practice. m) During construction work, including cutting of marbles, ambient noise level should not exceed more

D. Practices to be discarded for pollution free knylronmemt: .

a) Don't dispose of debris indiscriminately, b) Don't allow the vehicles to run at high speed within the work site. (\*,c) Don't cut materials without proper dust control/noise control facility. d) Don't keep materials without effective cover. e) bon't allow access in the work area except workers to limit soil disturbance and prevent access by: fencing, ditches, vegetation, berms or other suitable barrier. f) Don't linave the soil, sand and cement stack uncovered, Don't keep materials or debrts on the roads or pavements.

urning model tyres in hot mix plant as a fuel during construction and repair of the roads for melting Office of the coal far she uld be discarded: Executive Engineer, Br.-X The Kolhata Manisipal Corps. Building Department, Br.-X Dated 12/2/21