

PUBLIC DRAINAGE PURPOSE

SEMI U.G. WATER RESERVOIR

SOAK PIT

1800

1801

4491

3295

3371

3492

3555

canti. above W1

- 2300 LEV.

canti. above W1

13456

975

W1

14500

850 RAILING

W1

5725

COMMERCIAL SPACE +300 LEV.

4966

5655

1375

+300 LEV.

W1

CANTI. ABOVE

SEPTIC TANK

4168

LIFT 1200x1500

UP

1250

1500

1325

1920

1255

2730

3889

3125

2500

7 SHOP

TOILET 200x2175

+300 LEV.

1849

2125

1125

1074

2425

13 SHOP

- 2300 LEV.

CANTI. ABOVE

6150

2925

6 SHOP

1255

1671

1074

12340

900

2925

3100

5 SHOP

1800 WD CORRIDOR

2725

1325

2025

11 SHOP

3128

12 SHOP

2485

3665

2925

2700

9 SHOP

2000

2700

2700

2125

8 SHOP

775

10690

6125

3025

6125

2 SHOP

1800 WD CORRIDOR

2700

4000

1800

4550

4 SHOP

+300 LEV.

RAMP DOWN TO BASEMENT

7450

3050

1 SHOP

+300 LEV.

3450

4525

3050

3 SHOP

+300 LEV.

RAMP UP

RAILING

± 0.00 (PROPOSED GROUND LEV.)

FROM WATER MAIN

3500

22560

7.10 M. WIDE GARIA STN. ROAD

GROUND FLOOR PLAN