STATE LEVEL ENVIRONMENT IMPACT ASSESSMENT AUTHORITY

Pranisampad Bhaban, 5th floor, LB-2, Sector-III, Salt Lake, Kolkata-700 106. Telefax No. 033 2335 5246

Website: www.environmentwb.gov.in

Date: 13 /06 / 2019

No. 1126 / EN / T-II-1 /028/2018

To M/s Mahakosh Property Developers. 54/10, Debendra Chandra Dey Road 375, Prince Anwar Shah Road Kolkata – 700 015

SUB: Application for Environmental Clearance for the Proposed Residential-cum-SME Complex by M/s. Mahakosh Property Developers at 54/10, D.C. Dey Road, Kolkata $-700\,046$, West Bengal.

Sir,

This has reference to the application for Environmental Clearance (EC) signed hardcopy of which was submitted to SEIAA on 25.04.2018 on the above referred project and subsequent communications for Environmental Clearance for the proposed Residential-cum-SME complex at premises no. 54/10, D.C. Dey Road, Kolkata – 700 046, West Bengal.

The proposal has been examined and processed in accordance with the EIA Notification, 2006. The proposal is for construction of Residential-cum-SME complex comprising in 6(six) residential blocks (B+G+19) and one commercial block (B+G+10). Total built up area of the project is 177769.72 sq.mtr. The project proponent has obtained sanctioned building plan for the project vide Building Plan No. 2007070191 dated 20.03.2008.

The project is a violation case which started construction work without obtaining Environmental Clearance. Therefore the project proposal has been dealt as per MoEF&CC Notification No. S.O.804 (E) dated 14.03.2017, S.O.1030(E) dated 08.03.2018; Office Memorandum issued by MoEF&CC dated 15.03.2018 and 16.03.2018; and in accordance with EIA Notification, 2006.

SEIAA filed legal case against the project proponent for violation in Sealdah Court, South 24 Parganas (Case no.C-121/16). The case was disposed of by the Ld. Judicial Magistrate, Sealdah Court, by order dated 06.05.2016. The Hon'ble Court had imposed penalty, which was paid by project proponent.

The project proponent submitted remediation plan and natural and community resource augmentation plan of a total amount of Rs. 1,87,56,500/- (Rupees One crore eighty seven lac fifty-six thousand and five hundred only) which has been accepted by SEAC and SEIAA. The plan is attached herewith as annexure 1.

Proposed conditions for environmental clearance for the proposed residential cum SME complex at 54/10, D.C.Dey Road, Kolkata, West Bengal by M/s. Mahakosh Property Developers.

Salient features of the proposed project for which EC has been considered are as follows -

	alient features Proposed project		
Total Land Area	66345.09 sqm		
Net Land Area	65065.8 sqm		
Dwelling Units	796		
Expected Population	Total Population - 6480		
Total water Requirement	720 KLD (operation phase)		
Fresh Water requirement	400 KLD (KMC supply)		
Waste Water Generation	575 KLD (To be treated in STP)		
Reuse of treated waste water	370 KLD (To be reused after treatment in STP)		
Waste water discharge	150 KLD (To be discharged to KMC sewer line aft treatment in STP)		
Solid Waste Disposal	2 tonnes per day		
Total Built-up Area	177769.72 sq.mtr.		
Ground Coverage	11388.82 sq.mtr. (17.5%)		
Paved Area	15177.30 sqm (23.3%)		
Exclusive Tree plantation area			
No. of trees for plantation	At least 911 trees. In addition, existing trees to be		
Existing water Body	retained 1023.60 sqm (1.6%)		
No. of Car Parking	Covered -756 Open - 796, Total -1552		
Power requirement	9.8 MW, CESC. At least 1% of total demand load to be met from solar power source		
Backup Power	DG – 4 X 200 KVA, 6 X 500 KVA, 3 X 1500 KVA		
Project Cost	Rs. 375.13 Crores		
CER amount (Rs.)	1.5% of Rs. 375.13 Crores = Rs. 5.63 Crores		

State Level Environment Impact Assessment Authority (SEIAA), examined the proposal and also perused recommendations of the State Level Expert Appraisal Committee (SEAC). After due consideration of the project proposal, and after considering the recommendations of the State Level Expert Appraisal Committee (SEAC), the State Level Environment Impact Assessment Authority accords Environmental Clearance to the project as per provisions of the EIA notification no. S.O. 1533 (E) dt. 14th September, 2006 of Ministry of Environment & Forests, GOI, subject to strict compliance of terms and conditions as mentioned below.

Part A - SPECIFIC CONDITIONS

I. Construction Phase

- a) Steps to avoid disturbance during construction:-
- i. Topsoil should be stripped to a depth of 20 cm from the areas proposed for buildings, roads, paved areas and external services. Buildings shall be designed to follow the natural topography as much as possible. Minimum cutting and filling should be done.
- ii. All the topsoil excavated during construction activities should be under cover/stored by retaining walls for use in horticulture / landscape development within the project site. Adequate erosion and sediment control measures to be adopted before ensuing construction activities.
- iii. Prior permission should be obtained from the competent authority for demolition of the existing structure, if any. Waste recycling plans should be developed for prior to beginning of demolition and construction activity. The plans should identify wastes to be generated and designate handling, recycling and disposal method to be followed.
- iv. Disposal of muck including excavated material during construction phase should not create any adverse effects on the neighbouring communities and disposed off taking the necessary precautions for general safety and health aspects.
- v. Diesel generator sets during construction phase should have acoustic enclosures and should conform to E(P) Rules prescribed for air and noise emission standards.
- vi. Vehicles / equipment deployed during construction phase should be in good condition and should conform to applicable air and noise emission standards and should be operated only during non-peaking hours. Plastic/tarpaulin sheet covers shall be provided for vehicles bringing in sand, cement, murram and other construction materials prone to causing dust pollution at the site as well as taking out debris from the site.
- vii. Ambient noise levels should conform to residential standards both during day and night. Fortnightly monitoring of ambient air quality (PM, SO₂ and NO_x) and equivalent noise levels should be ensured during construction phase.
- viii. Construction spoils including bituminous material and other hazardous materials including oil from construction equipments must not be allowed to contaminate watercourses and the dump sites for such material must be secured so that they should not leach into the ground water. If necessary, oil trap should be installed where there is deployment of heavy machineries.
- ix. All construction and demolition debris shall be stored at the site (and not dumped on the roads or open spaces outside) before they are properly disposed. All demolition and construction waste shall be managed as per the provisions of the Construction and Demolition Waste Rules, 2016.
- x. Regular supervision of the above and other measures should be in place all through the construction phase so as to avoid disturbance to the surroundings. Discomfort in the neighbourhood due to the proposed project activity should be minimized as far as practicable.
- xi. Loading and unloading operations should not be carried out in open areas and should be preferably done during day time, if there is any major settlement in the surrounding areas. The construction activities including Piling work, Operation of Ready Mix Plant and Vibrator etc. should not be carried out during the night time (10 P.M. to 6 A.M.). Only essential operations, if any, may be carried out for a limited period during nighttime.
- xii. The proponent must ensure that no driven piles shall be proposed for this project, if there is any major settlement in the surrounding areas.
- xiii. Dust, smoke & other air pollution prevention measures shall be provided for the building as well as the site. These measures shall include screens for the building under construction, continuous dust / wind breaking walls all around the site (at least 3m height).

Member Secretary, State Level Environmental Impact Assessment Authority

Page 3 of 11

- xiv. Use of Ready-Mix concrete is recommended for this project.
- xv. Adequate measures to be adopted to avoid wastage of water for curing of concrete structures.
- xvi. Adequate mitigative measures should be adopted to control dust emissions, noise and vibrations from construction activities. Vehicles and construction machineries should be properly maintained. Vehicles should conform to Pollution under control (PUC) norms.
- xvii. Locally available materials with less transportation cost should be used preferably.
- xviii. Promotion of use of cleaner fuel and fuel quality improvement should be done. Excessive energy consumption and fuel usage should be avoided.
- xix. Accumulation / stagnation of water should be avoided to ensure vector control.

b) Selection of materials for better energy efficiency:-

- i. Use of energy efficient construction materials should be ensured to achieve the desired thermal comfort.
- ii. Design layout should ensure adequate solar access and ventilation. Proper planning and window design for daylight integration should be considered.
- iii. Fly Ash is to be used for construction as per Notification No. S.O. 763(E) dated 14.09.1999 amended vide Notification No. S.O. 979(E) dated 27.08.2003, S.O. 2804(E) dated 03.11.2009 and S.O.254(E) dated 25.01.2016 of the Ministry of Environment & Forests, Govt. of India.
- iv. Construction should conform to the requirements of local seismic regulations. The project proponent should obtain permission for the plans and designs including structural design, standard and specifications from
- v. Construction technologies that require less material and possess high strength should be adopted. Materials with low embodied energy and high strength should be used preferably.
- vi. The building will be constructed and provisioned to use natural sunlight to the maximum during the day
- vii. Use of alternate building materials and alternate construction techniques should be considered apart from the conventional materials and methods. Use of hollow unit masonry should be considered.
- viii. Use of environment friendly materials in bricks, blocks and other construction materials, shall be required for at least 20% of the construction material quantity. These include fly ash bricks, hollow bricks, AACs, Fly ash lime gypsum blocks, compressed earth blocks and other environment friendly materials.
- ix. Use of energy efficient lighting systems e.g. LED etc. should be promoted. Solar energy should be used for outdoor lighting. Adequate no. of solar lights should be installed for external lighting as per norms. All outdoor & common area lighting will be LED system.
- x. Solar water heating arrangement will be provided to meet 20% of the hot water demand of the commercial and institutional building and as far as possible for residential buildings.
- xi. Concept of passive solar design that minimize energy consumption in buildings by using design elements, such as building orientation, landscaping, efficient building envelope, appropriate fenestration, increased day lighting design and thermal mass etc. shall be incorporated in the building design.
- xii. Proper insulation of roof should be provided to achieve desired thermal comfort. Use of light coloured, reflective roofs having an SRI (solar reflectance index) of 50% or more should be incorporated.
- xiii. Use of high albedo or reflective pavements to keep parking lots, pavements and inside roads cool should be
- xiv. Guidelines to the occupants should include usage efficiency measures such as energy efficient lighting and
- xv. Reduce hard paving-onsite (open area surrounding building premises) and/or provide shade on hard paved surfaces to minimize heat island effect and imperviousness of the site.

- xvi. Adequate open space, greenery and water bodies to be provided as per rules.
- xvii. Compliance with the Energy Conservation Building Code (ECBC) of Bureau of Energy Efficiency shall be ensured.
- xviii. Any proposed building with air-conditioning facility should follow the norms proposed in the ECBC regulations framed by the Bureau of Energy Efficiency. Use of chillers will be CFC & HCFC free.
- xix. Restrict the use of glazed surface as per National Building Code 2005 and as amended thereafter.
- xx. Wall, window and roof u-values shall be as per ECBC specifications.
- xxi. At least 1% of total demand load to be met from solar power source.

c) Water Body Conservation: -

- i. Existing water body of 1023.60 sqm. (1.6% of land area) should not be lined and the embankment should not be cemented. The water body is to be kept in natural condition without disturbing the ecological habitat.
- ii. No construction is allowed on wetland and water bodies.

d) Plantation Proposal: -

- i. The unit should strictly abide by The West Bengal Trees (Protection and Conservation in Non-Forest Areas) Act, 2006 and subsequent rules. The proponent should undertake plantation of trees over at least 20% of the total area.
- ii. No tree can be felled without prior permission from the Tree Cutting Authority constituted as per the West Bengal Trees (Protection and Conservation in Non-Forest Areas) Act, 2006 and subsequent rules.
- iii. The proponent should plant at least 911 trees. Existing trees to be retained. The landscape planning should include plantation of native species. The species with heavy foliage, broad leaves and wide canopy cover are desirable. Water intensive and/or invasive species should not be used for landscaping. Indicative list of tree species for plantation is given as annexure-2
- iv. Provision for Roof Top Gardening is mandatory.

e) Water supply: -

i. Water requirement during construction phase shall be met from Kolkata Municipal Corporation supply. Ground water should not be abstracted without prior permission from the competent authority as per the West Bengal Ground Water Resources (Management, Control and Regulation) Act, 2005.

f) Sewage Treatment Plant:-

i. As per the proposal during construction phase construction water must be treated and reused. Domestic waste water generated during construction phase must be treated in a septic tank followed by soak pit.

g) Storm water Management & Mitigation of Heat Island Effect:-

- i. Imperviousness of the site shall not exceed the NBC (National Building Code 2005 and as amended thereafter) standards for imperviousness factor applicable to different types of area.
- ii. At least 20% of the open spaces shall be pervious. Use of Grass pavers, paver blocks with at least 50% opening, landscape etc. would be considered as pervious surface.
- iii. Total paved area of site under parking, roads, paths or any other use should not exceed 25% of the site area.
- iv. Adequate storm water drainage network to be designed for the project without disturbing the surrounding settlements. Storm water management plan should be implemented so as to prevent sudden discharge of excessive volumes of storm water to the receiving waters thus reducing the shock load on the drainage system and impact on receiving water body.
- v. The natural drain system should be maintained for ensuring unrestricted flow of water. No construction shall be allowed to obstruct the natural drainage through the site.

Member Secretary, State Level Environmental Impact Assessment Authority

Page 5 of 11

- vi. Disruption to the natural hydrology of the site should be minimised by reducing impervious cover, increasing on site infiltration and managing storm water run off.
- vii. Heat island effect should be minimized by use of shading or reflective surfaces, mainly the surfaces that contribute to the heat island effect i.e. streets, sidewalks, parking lots and buildings. White roofs should be

h) Rain Water Harvesting Scheme: -

- i. A rain water harvesting plan needs to be designed where the recharge bores of minimum one recharge bore per 5,000 square meters of built up area and storage capacity of minimum one day of total fresh water
- ii. The proponent must collect rainwater from roof-top catchments and reuse for various purposes after necessary cleaning. Adequate retention time and storage provisions should be provided for harvesting
- iii. All recharge should be limited to shallow aquifer.

i) Solid Waste Management: -

- i. Conform to the guidelines on Environment Management of Construction & Demolition Waste by CPCB,
- ii. Adequate provision shall be made for storage and segregation of solid waste and adequate means of access
- iii. All construction and demolition debris shall be stored at the site (and not dumped on the roads or open spaces outside) before they are properly disposed. All demolition and construction waste shall be managed as per the provisions of the Construction and Demolition Waste Rules, 2016.

j) Transport Management: -

- Internal traffic planning and management should be adequate to ensure uninterrupted traffic movement in the
- ii. Clarified Wastewater will be used for sprinkling water on the unpaved internal roads on a regular basis.

k) Others: -

- i. Notification G.S.R. 94(E) dated 25.01.2018 issued by MoEF & CC, Government of India should be
- ii. Conform to the clause mentioned in the "Manual and standards for EC for large construction projects" published by MoEF & CC, Government of India.
- iii. All mandatory approvals and permission as required from Director of Explosives, Fire Department etc.
- iv. Efficient management of indoor air quality must be ensured for health and safety of the users.
- v. Adequate measures to be adopted for water conservation during construction and operation stage. Use of efficient irrigation equipment, evaporative cooling unit in air-conditioning system etc. should be considered.
- vi. Rest room facilities should be provided for service population.

II Operation Phase

a) Water supply: -

i. Water requirement shall be met from Kolkata Municipal Corporation supply. Ground water should not be abstracted without prior permission of the competent authority as per the West Bengal Ground Water Resources (Management, Control and Regulation) Act, 2005.

ii. Use of water meter conforming to ISO standards should be installed at the inlet point of water uptake to monitor the daily water consumption. Use of water efficient devices / fixtures and appliances should be promoted. Installation of dual flushing system should be considered to conserve water.

iii. The proponent must practice rainwater harvesting on regular basis.

b) Sewage Treatment Plant:-

- i. As per the proposal submitted by the proponent, waste water shall be treated in STP. Treated waste water shall be partly reused for landscaping, flushing and car washing etc. and rest will be discharged to municipal sewer. Necessary permission from the Competent Authority to be obtained.
- ii. Reuse of treated wastewater should be carried out as proposed.

c) Emission from Diesel Generator Set: -

- i. Noise barriers will be provided at appropriate locations so as to ensure that the noise levels do not exceed the prescribed standards. Diesel generator sets should be provided with integral acoustic enclosure at the manufacturing stage itself as per CPCB norms.
- ii. The stack height and emissions from D.G. sets should conform to the norms of Central Pollution Control Board. The certification of space design for DG sets should be done by competent authority.

d) Ensure Energy Efficiency:-

- i. Use of energy efficient construction materials to achieve the desired thermal comfort should be incorporated. The desired level of R and U factors must be achieved. U factor for the top roof should not exceed 0.4 Watt/sq.m/degree centigrade with appropriate modifications of specifications and building technologies. The provisions of National Building Code 2005 and as amended thereafter should be strictly followed.
- ii. Use of energy efficient electrical systems should be promoted. High efficiency lamps with electronic ballasts should be used.
- iii. Energy efficient Motors and properly rated Transformers should be installed. Manufacturer's certificate to this effect shall be obtained and kept on record. Back up power supply should be based on cleaner fuel.
- iv. The power cabling shall be adequately sized as to maintain the distribution losses not to exceed 1% of the total power usage. Record of transmission losses shall be maintained. The proponent shall install permanent electrical metering to record demand (kVA), energy (kWh) and total power factor.
- v. At least 1% of total demand load to be met from solar power source.

e) Transport Management: -

i. Use of public mode of transportation should be promoted. Use of the least polluting type of transportation should be promoted. Adequate parking space should be provided as per norms.

ii. Pathways should be covered or shadowed by tree canopy as far as practicable. Transport system should be such that traffic will be calm in neighbourhoods. Traffic within the project site should be restricted by telecommunication lines should be provided.

f) Solid Waste Management:-

- i. The proponent should abide by the Solid Waste Management Rules, 2016. The proponent must develop the Solid Waste Management and Disposal Scheme ensuring storage and segregation of biodegradable and non-biodegradable wastes. The solid waste is to be disposed off in consultation with concerned authority.
- ii. The proponent shall install onsite compost plant for treatment of biodegradable part of Municipal Solid Waste. Sufficient space for installation of onsite compost plant should be provided and operation of the compost plant considering full occupancy of the apartments i.e. the capacity of garbage disposal unit should be selected accordingly.
- iii. The handling agency should also take care of the recyclable wastes like plastic, paper board, glass etc. and also inert materials in case of respective municipal authorities want to avoid any kind of waste from the housing complex.
- iv. The proponent should have sufficient area for horticulture where the compost generated can be used as fertilizer and soil supplement and also have arrangement for sale of excess quantity of compost.
- v. Provision for treatment of leachate generated and odour control in on-site compost plant should be made.
- vi. Non-recyclable inorganics and rejects will be disposed off through concerned authority as proposed.
- vii. The proponent should provide different coloured bins for different categories of waste and ensure complete segregation of biodegradable and non-biodegradable wastes. The solid waste from different collection and storage bins should be finally collected at transfer stations. Further segregation will be done at transfer stations to collect recyclables such as plastic, polythene, glass, metals, textiles, rubbers, leathers, paper etc. Separate compartments shall be provided for each type of recyclables.
- viii. The proponent should abide by the Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016. Collection and storage of hazardous wastes during Pre-construction and Post-construction activity should be planned properly. The expected hazardous wastes should be disposed off separately as per the Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016.
- ix. Spent oil from DG Sets should be stored in HDPE drums in isolated covered facility and disposed off as per the Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016. Spent oil from DG Sets should be disposed off through registered recyclers only.
- x. The provisions of the Solid Waste Management Rules, 2016 and the E-waste (Management) Rules, 2016 and the Plastic Waste Management (Amendment) Rules, 2018 shall be followed.

g) Others:-

- The implementation of Environmental Management Plan should be carried out, as proposed. Regular monitoring should be carried out during construction and operation phases.
- ii. The project proponent should provide guidelines to the users to ensure conservation of energy and water. In-house environmental awareness campaigns should be carried out at regular intervals to ensure environmental protection.
- iii. Fire fighting systems should be designed in compliance with the WBFS and NBC norms. Preventive measures should be adopted for Risk & Disaster Management as per the provisions of the National Building Code 2005 and as amended thereafter.

- iv. Corporate Environment Responsibility (CER) Program to be formulated based on the results of socio economic survey on relevant parameters and need assessment of local people as per MoEF OM no. F.No.22-65/2017-IA.III dated: 1st May, 2018.
- v. The proponent should abide by the Direction issued by the Department of Environment, Government of West Bengal, vide No. EN/3170/T-IV-7/001/2009 dated 10.12.2009.
- vi. Environmental Management Information System shall be maintained properly.
- vii. The proponent should restrict the use of glazed surface as per National Building Code 2005 and as amended thereafter.
- viii. All the recommendation made in the EIA/EMP report should be complied with.

Part-B GENERAL CONDITIONS

- i. The environmental clearance accorded shall be valid for a period of 7 years for the proposed project.
- ii. Prior Consent-to-Establish (NOC) for the proposed project must be obtained from WBPCB by the proponent. All other statutory clearances should be obtained by project proponent from the competent authorities.
- iii. The proponent should maintain a display board at the site, providing detailed information on the salient features of the proposed project.
- iv. The environmental safeguards contained in the EIA/EMP report should be implemented in letter and spirit.
- v. All the conditions, liabilities and legal provisions contained in the EC shall be equally applicable to the successor management of the project in the event of the project proponent transferring the ownership, maintenance of management of the project to any other entity.
- vi. The project proponent should make financial provision in the total budget of the project for implementation of the suggested safeguard measures.
- vii. Six monthly compliance reports should be submitted to the West Bengal Pollution Control Board as well as the Regional Office of MoEF&CC, Bhubaneswar who would be monitoring the implementation of environmental safeguards and should be given full cooperation, facilities and documents / data by the project proponents during their inspection. A complete set of all the documents should also be forwarded to the State Environmental Impact Assessment Authority, West Bengal.
- viii. In case of any violation of the conditions laid down in this Environmental Clearance, Section 16 of The Environment (Protection) Act, 1986, will be applicable.
- ix. In case of any change(s) in the scope of the project, the project would require a fresh appraisal by the SEIAA, West Bengal.
- x. The State Environmental Impact Assessment Authority, West Bengal reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time-bound and satisfactory manner.
- xi. The Project Proponent should inform the public that the proposed project has been accorded environmental clearance by the SEIAA, West Bengal and copies of the clearance letter are available with the State Pollution Control Board / Committee and may also be seen at website of the SEIAA, West Bengal (http://environmentwb.gov.in). This should be advertised within seven days from the date of

Member Secretary, State Level Environmental Impact Assessment Authority

Page 9 of 11

issue of the clearance letter, at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locality concerned.

- Provision for incorporation of appropriate conditions in the Sale Agreement / Deed, for ensuring XII. sustained Operation and Maintenance (O&M) of the common facilities (STP, Rainwater harvesting system, Solid waste management system, Solar street lights etc.) even after transfer of ownership of the project, should be made in explicit and transparent manner.
- The above stipulations would be enforced along with those under the Water (Prevention and Control of xiii. Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986, the Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016, the Public Liability Insurance Act, 1991, the Environment Impact Assessment Notification
- The contact details of the proponent and the name of the consultant are given below xiv.

Name of the Contact person with Designation	Mr. Shailendra Kothari, Sr. Manager - Admin	
Address	54/10, Debendra Chandra Dey Road, Kolkata - 70001	
Email	shailendra_kothari@ruchirealty.com	
Telephono Number T 31	033 66066777 ; 033 23296958	
None - Col E :	M/s Perfact Enviro Solutions Pvt. Ltd.	

Yours sincerely.

(Niraj Singhal, IFS) Chief Environment Officer & Member Secretary, SEIAA

Date: 13 / 06/2019

No. 1126/1(4) /EN/ T-II-1/028/2018 Copy forwarded to:-

1. Secretary, SEAC & M.S. WBPCB

2. Officer-in-Charge, Regional Office (Eastern Zone), Ministry of Environment & Forests, Government of India, A-3, Chandrashekharpur, Bhubaneswar - 751 023, Orissa.

3. Member Convener, Monitoring Committee for Environmental Clearance, WBPCB.

4. Guard file / Record file.

Sd/-Chief Environment Officer & Member Secretary, SEIAA

Annexure – 1
REMEDIATION PLAN AND NATURAL & COMMUNITY RESOURCE AUGMENTATION PLAN.

SI. No.	Item	Number of units	Amount
1.	Amount of contribution toward buying E-Rickshaws		Rs. 1,68,75,000/-
2.	Fund Allocation for Greening Activity (WBFDCL/WBWDCL/SFDA)		Rs. 18,81,500/-
Total			Rs. 1,87,56,500

Annexure - 2

LIST OF TREES FOR PLANTATION

Sl. No.	BOTANICAL NAME	COMMON NAME	QUANTITY
1.	Mimusops elengi	Bakul	100
2.	Lagerstroemia speciosa	Jarul	100
3.	Alstonia scholaris	Chatim	100
4.	Bauhinia variegata	Kanchan	100
5.	Cassia fistula	Amaltus	100
6.	Delonix regia	Gulmohor	11
7.	Thespesia populnea	Poros	40
8.	Azadinacta indica	Neem	25
9.	Michelia champaca	champa	35
10.	Polyalphia longifolia	Devdaru	300
Total			911

Onmental Impact Accomment Authority